3M™ Tape Primer 94, Light Yellow, 1/2 Pint, 12 Each/Case

3M Product Number 94, 3M ID 7100003276, UPC 00021200239267 0.0 (0)

Details | Typical Properties | Resources | Reviews | Support





Hover over image to zoom in

Promotes adhesion to polyethylene, polypropylene, ABS, PET/PBT blends and other on difficult to stick to substrates

Commonly used for increasing adhesion of film and vinyl graphics in automotive detailing

Can be applied with brush or swab for small areas and a pressurized flow gun for larger areas

View more details

Frequently viewed resources

Tech Data Sheet (1)

Safety Data Sheet (PDF, 0B)

View all resources

For industrial/occupational use only. Not for consumer sale or use.

Change options

Volume (Metric)	236 mL
Volume (Imperial)	0.5 pt
Surface Type	Plastic
Product Type	Primer
Adhesive Type	General Purpose Acrylic Adhesive
Composition	Solvent Based

Large Volume Order

Ask a 3M Expert

Feedback

Details

Highlights

- Promotes adhesion to polyethylene, polypropylene, ABS, PET/PBT blends and other on difficult to stick to substrates
- Commonly used for increasing adhesion of film and vinyl graphics in automotive detailing
- Can be applied with brush or swab for small areas and a pressurized flow gun for larger areas
- Dries to a clear finish
- Cleans up with isopropyl alcohol

3M™ Tape Primer 94 can be used to improve the overall adhesion of tape, film and vinyl graphics to polyethylene, polypropylene, ABS, PET/PBT blends, concrete, wood, glass, metal and painted metal surfaces.

Dries in Minutes for Efficient Use
Make sure your surface is clean and dry before applying a thin, uniform coat of 3M™ Tape Primer 94. The primed surface must remain free from contaminants prior to applying the tape. It's important to use the minimum amount of product necessary as over applying can cause sub-optimal results. Allow the primer to dry completely, which is usually accomplished in 5 minutes at room temperature, before applying tape. Special note: porous surfaces may require 2 applications for uniform coverage and good adhesion. Allow your first application of primer to dry before applying a second coat.

Recommended Applications

- Promote adhesion of 3M™ VHB™ Tape
- For use on many plastic, rubber, painted and bare metal substrates

Application Tips
3M™ Tape Primer 94 may be applied with a brush, swab, pressurized flow gun, knurled roller or similar type of equipment and can be removed with isopropyl alcohol. Vigorous scrubbing may be required.

Typical properties

Details

Adhesive Type	General Purpose Acrylic Adhesive
Application	Exterior Side Panel Bonding, Wall & Door Panel Attachment
Application Temperature-Environment	60°F -80°F
Application Temperature-Environment (Metric)	15°C - 27°C
Brands	3M™
Clean-up	Acetone Solvent
Composition	Solvent Based
Full Cure Time	2 min
Industries	General Industrial, Transportation
Net Weight (Imperial)	0.59 lb
Net Weight (Metric)	0.27 kg
Physical Form	Liquid
Product Form	Can, Each
Product Type	Primer
Shelf Life in Months (From Date of Manufacture)	18
Storage Temperature	60°F - 80°F
Storage Temperature (Celsius)	15°C - 27°C
Surface Type	Plastic
Units per Case	12.0
Volume (Imperial)	0.5 pt
Volume (Metric)	236 mL

Dimensions and Classifications

Overall Height (Imperial)	2.88 in
Overall Height (Metric)	7.3 cm
Overall Length (Imperial)	2.88 in

Resources

Safety Data Sheets (1) | Regulatory Data Sheet (1) | Brochures (1)

3M™ Primer 94

Safety Data Sheets (PDF, 0B)

Reviews

Reviews

Review this Product

Be the first to review this product

Large Volume Order

All fields are required unless indicated optional.

Business Email Address

First Name

Last Name

Job Role
Select One

Phone Number
201-555-0123

Company Name

Company Type
Select One

Country/Region
United States

Company Address

City

State/Province
Select One

Zip Code/Postal Code

Industry
Select One

Application Purpose
Select One

Application Type
Select One

Substrate
Select One

Additional information about your request (optional)

Subscribe to 3M marketing communications

3M takes your privacy seriously. 3M and its authorized third parties will use the information you provided in accordance with our Privacy Policy to send you communications which may include promotions, product information and service offers. Please be aware that this information may be stored on a server located in the U.S. If you do not consent to this use of your personal information, please do not use this system.

SUBMIT

For industrial/occupational use only. Not for consumer sale or use.

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action, or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert.

3M Legal | Privacy | HIPAA Privacy | CMCA | Accessibility Statement | Your Privacy Choices
© 3M 2022. All Rights Reserved.
The brands listed above are trademarks of 3M.