DATA SHEET N° DS/356	*SI2KSYS1US* THERMO TRANSFER MARKING SYSTEM	DATE: 01/06/09



Item Code: SI2KSYS1US

GENERAL CHARACTERISTICS

Thermo transfer printer suitable to mark components inside and outside cabinets.
The printer is supplyed with automatic feeder.
Reduced maintenance, high quality of printing, high speed of printing, no startup time required, items just ready to be applyed after printing phase and easyness of use fulfill Marking System Market requirements.
Fully compatible with software Simplo.

TECHNICAL FEATURES

Type	Desktop thermal transfer printer
Printing Process	Thermal transfer technology
Feeding Process	Supplied with Automatic Feeder
Feeding Mode	Stack, Single and Plate
Printing Resolution	300 DPI
Printable Area	W54 x L496 mm
Max Item consumable size	W80 x L500 mm
Outside dimensions	W423mm x D240mm x H208mm
Weight	9,5 Kg
Windows Compatibility	Windows 95, 98, 2000, NT (service pack 6), XP, Vista
Available Fonts	True-Type Fonts
Compatibility	Image formats (gif, jpg, jpeg, bmp, wmf)
Printing Speed	1 printing each 28 secs
Print Ribbons	SI2KSBN/B - Strong black, SI2KRBN/R - Red Ribbon for Pvc and Metacrylate tags SI2KRBN/RS - Red ribbon for Stack SI2KRBN/S - Silver, SI2KRBN/W - White
Print surface cleaning System	SI2K0003 -Cleaner Roller, SI2KCLEAN -Cleaning tape
Interface	Conforming to Centronics (IEEE 1284-1294) Std
Operating Environment	5°C-32,5°C 15%RH-80%RH
Storage environment	5°C-35°C 35%RH-85%RH
Power Supply	100V to 240V AC
Power Consumption	45W
Display	LCD panel (16 columns x 2 lines)
Built-in keyboard	To set Feeder Mode and Test Mode.
Available Accessories:	SI2K0013N - Card Store
	SISK0014NP1 - Support Plate for Cable tags
	SI2K0017 - Support Plate for TB tags
	SIMPLOHIP - Software for Marking System
	SI2K0010 - Parallel Cable (IEEE 1284-1294) Std
	SI2K0019 - Converter cable Usb-Parallel Port
	SI2K0025 - Power supply cable for USA
	SI2K0016 - Support base for SI2KPRINTUNO
On demand accessory:	SI2K0013NAD -Adapter for Card Store for 30mm Cable tags