Click here to ask an associate for production status of specific part numbers.

Low-Noise, High-Precision Series Voltage References

MAX6070/MAX6071

General Description

The MAX6070/MAX6071 offer a very low noise and low-drift voltage reference in a small 6-pin SOT23 package. These devices provide a 1/f noise voltage of only 4.8µV$_{P-P}$ at an output voltage of 2.5V, with a temperature drift of 6ppm/°C (max, A grade). The devices consume 150µA of supply current and can sink and source up to 10mA of load current. The low-drift and low-noise specifications enable enhanced system accuracy, making these devices ideal for high-precision industrial applications. The MAX6070 offers a noise filter option for wideband applications.

The devices are available in a 6-pin SOT23 package and are specified over the extended industrial temperature range of -40°C to +125°C. The 2.5V options are also available in a 6-bump 0.78mm x 1.41mm wafer-level package (WLP).

Applications

- High-Accuracy Industrial and Process Control
- Precision Instrumentation
- High-Resolution ADCs and DACs
- Precision Current Sources
- Automotive

Benefits and Features

- 6-Pin SOT23 Package Reduces System Board Space
- Stable Performance over Temperature and Time Improves System Accuracy
  - High ±0.04% Initial Accuracy
  - Low 1.5ppm/°C (typ), 6ppm/°C (max, A grade) Temperature Drift
  - Low 4.8µV$_{P-P}$ Noise (0.1Hz to 10Hz) at 2.5V
  - Low 200mV Dropout Voltage
  - High 85dB Ripple Rejection
- Low 150µA Supply Current Reduces Power Consumption
- Filter Option Lowers High-Frequency Noise
- Output Options: 1.25V, 1.8V, 2.048V, 2.5V, 3.0V, 3.3V, 4.096V, and 5.0V Cover Common Voltage Levels for a Wide Variety of Applications
- 0.78mm x 1.41mm WLP with 0.35mm Bump Spacing
- AEC-Q100 Qualified (Refer to *Ordering Information*)

***Ordering Information* and *Selector Guide* appear at end of data sheet.**

Typical Operating Circuits



19-6355; Rev 19; 9/24

© 2024 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.

Absolute Maximum Ratings

OUTF to GNDS, GNDF, GND ..... -0.3V to the lower of (V_{IN} + 0.3V), +6V
OUTS to GNDS, GNDF, GND .....-0.3V to +6V
IN to GNDS, GNDF, GND .....-0.3V to +6V
EN to GNDS, GNDF, GND .....-0.3V to +6V
FILTER to GND ..... -0.3V to the lower of (V_{IN} + 0.3V), +6V
GNDS to GNDF .....-0.3V to +0.3V

Continuous Power Dissipation (T_A = +70°C)
SOT23 (derate 4.3mW/NC above +70°C)..... 347.8mW
WLP (derate 10.2mW/NC above 70°C.....816mW
Operating Temperature Range..... -40°C to +125°C
Junction Temperature.....+150°C
Storage Temperature Range..... -65°C to +150°C
Soldering Temperature (reflow).....+260°C
Lead Temperature (soldering, 10s) .....+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Package Information

6 SOT23

PACKAGE CODE	U6+5/U6+5A
Outline Number	21-0058
Land Pattern Number	90-0175
Thermal Resistance, Multi-Layer Board:	
Junction to Ambient (θ_{JA})	230°C/W
Junction to Case (θ_{JC})	76°C/W

6 Thin WLP

PACKAGE CODE	N60B1+1
Outline Number	21-0744
Land Pattern Number	Refer to Application Note 1891
Thermal Resistance, Multi-Layer Board:	
Junction to Ambient (θ_{JA})	98°C/W

For the latest package outline information and land patterns (footprints), go to www.analog.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to www.analog.com/thermal-tutorial.

Electrical Characteristics—MAX607__AUT12 (V_{OUT} = 1.250V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
		MAX6070D, T_A = +25°C		-0.2		+0.2	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
		MAX6070D				20	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		13	100	µV/V
			T_A = T_{MIN} to T_{MAX}			125	
Load Regulation		0mA < I_{OUT} < 10mA, sink			70	150	µV/mA
		0mA < I_{OUT} < 10mA, source			100	150	
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			35		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			3.6		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			5.0		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			2.5		
Ripple Rejection		Frequency = 60Hz			100		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		6		ms
			MAX6071		20		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		6		ms
			MAX6071		60		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		2.7		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			130	200	µA
		T_A = T_{MIN} to T_{MAX}				260	
Shutdown Supply Current	I_{SD}					6	µA
ENABLE							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT18 (V_{OUT} = 1.800V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		35	150	µV/V
			T_A = T_{MIN} to T_{MAX}			200	
Load Regulation		0mA < I_{OUT} < 10mA, sink			120	200	µV/mA
		0mA < I_{OUT} < 10mA, source			120	200	
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			35		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			6		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz C_{OUT} = 0.1µF			7		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			5		
Ripple Rejection		Frequency = 60Hz			89		dB
Turn-On Settling Time	t_R	Settling to 0.01% C_{OUT} = 0.1µF	MAX6070 C_{FILTER} = 0.1µF		6		ms
			MAX6071		32		µs
Enable Settling Time	t_{EN}	Settling to 0.01% C_{OUT} = 0.1µF	MAX6070 C_{FILTER} = 0.1µF		6		ms
			MAX6071		60		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		2.7		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			130	200	µA
		T_A = T_{MIN} to T_{MAX}				260	
Shutdown Supply Current	I_{SD}					6	µA
ENABLE							
Enable Input Current	I_{EN}			-1		1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT21 (V_{OUT} = 2.048V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		50	180	µV/V
			T_A = T_{MIN} to T_{MAX}			225	
Load Regulation		0mA < I_{OUT} < 10mA, sink			135	225	µV/mA
		0mA < I_{OUT} < 10mA, source			135	225	
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			35		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			6.4		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz C_{OUT} = 0.1µF			8.6		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			6.3		
Ripple Rejection		Frequency = 60Hz			86		dB
Turn-On Settling Time	t_R	Settling to 0.01% C_{OUT} = 0.1µF	MAX6070 C_{FILTER} = 0.1µF		6.2		ms
			MAX6071		25		µs
Enable Settling Time	t_{EN}	Settling to 0.01% C_{OUT} = 0.1µF	MAX6070 C_{FILTER} = 0.1µF		6.2		ms
			MAX6071		65		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		2.7		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			130	200	µA
		T_A = T_{MIN} to T_{MAX}				260	
Shutdown Supply Current	I_{SD}					6	µA
ENABLE							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}				0.3 x V_{IN}		

Electrical Characteristics—MAX607__AUT25 (V_{OUT} = 2.500V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
		MAX6070D, T_A = +25°C		-0.2		+0.2	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
		MAX6070D				20	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		60	145	µV/V
			T_A = T_{MIN} to T_{MAX}			175	
Load Regulation		0mA < I_{OUT} < 10mA, sink			80	140	µV/mA
		0mA < I_{OUT} < 10mA, source			75	125	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 3)			110	230	mV
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			40		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			4.8		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			6		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			3		
Noise Spectral Density		MAX6071 thermal noise, f = 1kHz, C_{OUT} = 0.1µF			60		nV/√Hz
		MAX6070 thermal noise, f = 1kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			30		
Ripple Rejection		Frequency = 60Hz			84		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		30		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		75		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		2.8		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			150	235	µA
		T_A = T_{MIN} to T_{MAX}				300	
Shutdown Supply Current	I_{SD}				0.6	6	µA

Electrical Characteristics—MAX607__AUT25 (V_{OUT} = 2.500V) (continued)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
ENABLE/SHUTDOWN						
Enable Input Current	I_{EN}		-1		+1	µA
Enable Logic-High	V_{IH}		0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}				0.3 x V_{IN}	

Electrical Characteristics—MAX607__ANT25 (V_{OUT} = 2.5V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{IN} = C_{OUT} = 0.1µF, T_A = 0°C to +85°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		T_A = +25°C		-0.1		+0.1	%
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}				2.7	10	ppm/°C
Line Regulation		Over specified V_{IN} range	T_A = +25°C		60	300	µV/V
			T_A = T_{MIN} to T_{MAX}			350	
Load Regulation		0mA < I_{OUT} < 10mA, sink			80	200	µV/mA
		0mA < I_{OUT} < 10mA, source			75	180	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 3)			110	230	mV
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			16		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			4.8		$µV_{P-P}$
		10Hz to 10kHz, C_{OUT} = 0.1µF			6		$µV_{RMS}$
Noise Spectral Density		f_{SW} = 1kHz, C_{OUT} = 0.1µF			60		$nV/\sqrt{Hz}$
Ripple Rejection		Frequency = 60Hz			84		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF			30		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF			75		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		2.8		5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			160	250	µA
		T_A = T_{MIN} to T_{MAX}				320	
Shutdown Supply Current	I_{SD}				0.6	6	µA
ENABLE/SHUTDOWN							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT30 (V_{OUT} = 3.000V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
		MAX6070D, T_A = +25°C		-0.2		+0.2	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
		MAX6070D				20	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		90	200	µV/V
			T_A = T_{MIN} to T_{MAX}			260	
Load Regulation		0mA < I_{OUT} < 10mA, sink			90	170	µV/mA
		0mA < I_{OUT} < 10mA, source			90	150	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 3)			80	150	mV
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			40		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			4.6		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			7.8		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			5.0		
Ripple Rejection		Frequency = 60Hz			80		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		9.7		ms
			MAX6071		40		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		9.7		ms
			MAX6071		75		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		3.2		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			150	235	µA
		T_A = T_{MIN} to T_{MAX}				300	
Shutdown Supply Current	I_{SD}				0.6	6	µA
ENABLE/SHUTDOWN							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__ AUT33 (V_{OUT} = 3.300V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
		MAX6070D, T_A = +25°C		-0.2		+0.2	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
		MAX6070D				20	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		90	220	µV/V
			T_A = T_{MIN} to T_{MAX}			285	
Load Regulation		0mA < I_{OUT} < 10mA, sink			100	190	µV/mA
		0mA < I_{OUT} < 10mA, source			100	165	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 3)			65	150	mV
Output Current	I_{OUT}			-10		10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			40		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			10		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			9		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			6		
Ripple Rejection		Frequency = 60Hz			78		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		42		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		75		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		3.5		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			160	240	µA
		T_A = T_{MIN} to T_{MAX}				330	
Shutdown Supply Current	I_{SD}				0.6	6	µA
ENABLE/SHUTDOWN							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT41 (V_{OUT} = 4.096V)

(V_{IN} = +5.0V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
		MAX6070D, T_A = +25°C		-0.2		+0.2	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
		MAX6070D				20	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		100	250	µV/V
			T_A = T_{MIN} to T_{MAX}			350	
Load Regulation		0mA < I_{OUT} < 10mA, sink			125	225	µV/mA
		0mA < I_{OUT} < 10mA, source			135	225	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 3)			75	150	mV
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			35		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			9.6		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			12		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			9		
Ripple Rejection		Frequency = 60Hz			80		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		40		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		85		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		4.3		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			150	235	µA
		T_A = T_{MIN} to T_{MAX}				350	
Shutdown Supply Current	I_{SD}					6	µA
ENABLE							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT50 (V_{OUT} = 5.000V)

(V_{IN} = +5.5V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
OUTPUT							
Output Voltage Accuracy		MAX6070A/MAX6071A, T_A = +25°C		-0.04		+0.04	%
		MAX6070B/MAX6071B, T_A = +25°C		-0.08		+0.08	
Output Voltage Temperature Drift (Note 2)	TCV_{OUT}	MAX6070A/MAX6071A			1.5	6	ppm/°C
		MAX6070B/MAX6071B			2.0	8	
Line Regulation		Over specified V_{IN} range	T_A = +25°C		200	400	µV/V
			T_A = T_{MIN} to T_{MAX}			500	
Load Regulation		0mA < I_{OUT} < 10mA, sink			160	275	µV/mA
		0mA < I_{OUT} < 10mA, source			160	275	
Dropout Voltage		I_{OUT} = 10mA, T_A = T_{MIN} to T_{MAX} (Note 5)			60	150	mV
Output Current	I_{OUT}			-10		+10	mA
Short-Circuit Current	I_{SC}	Sourcing to ground			25		mA
		Sinking from V_{IN}			25		
Long-Term Stability		1000 hours at T_A = +25°C			35		ppm
Thermal Hysteresis		(Note 4)			85		ppm
DYNAMIC CHARACTERISTICS							
Noise Voltage	e_{OUT}	1/f noise, 0.1Hz to 10Hz, C_{OUT} = 0.1µF			9		$µV_{P-P}$
		MAX6071 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF			15		$µV_{RMS}$
		MAX6070 thermal noise, 10Hz to 10kHz, C_{OUT} = 0.1µF, C_{FILTER} = 0.1µF			12		
Ripple Rejection		Frequency = 60Hz			74		dB
Turn-On Settling Time	t_R	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		50		µs
Enable Settling Time	t_{EN}	Settling to 0.01%, C_{OUT} = 0.1µF	MAX6070, C_{FILTER} = 0.1µF		10		ms
			MAX6071		100		µs
Capacitive-Load Stability Range		I_{OUT} ≤ 10mA		0.1		10	µF
INPUT							
Supply Voltage	V_{IN}	Guaranteed by line regulation		5.2		5.5	V
Quiescent Supply Current	I_{IN}	T_A = +25°C			160	250	µA
		T_A = T_{MIN} to T_{MAX}				330	
Shutdown Supply Current	I_{SD}					6	µA
ENABLE							
Enable Input Current	I_{EN}			-1		+1	µA
Enable Logic-High	V_{IH}			0.7 x V_{IN}			V
Enable Logic-Low	V_{IL}					0.3 x V_{IN}	

Electrical Characteristics—MAX607__AUT50 (V_{OUT} = 5.000V) (continued)

(V_{IN} = +5.5V, I_{OUT} = 0mA, C_{OUT} = 0.1µF, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

Note 1: Limits are 100% production tested at T_A = +25°C. Specifications where T_A < +25°C or T_A > +25°C are guaranteed by design and characterization.

Note 2: Temperature coefficient is calculated using the “box method” which measures temperature drift as the maximum voltage variation over a specified temperature range. The unit of measurement is ppm/°C.

Note 3: Dropout voltage is defined as the minimum differential voltage (V_{IN} - V_{OUT}) at which V_{OUT} decreases by 0.2% from its original value at V_{IN} = 5.0V.

Note 4: Thermal hysteresis is defined as the change in +25°C output voltage before and after cycling the device from T_{MAX} to T_{MIN}.

Note 5: Dropout voltage is defined as the minimum differential voltage (V_{IN} – V_{OUT}) at which V_{OUT} decreases by 0.2% from its original value at V_{IN} = 5.5V.

Typical Operating Characteristics

(T_A = +25°C, unless otherwise noted.)

MAX6071_12 OUTPUT VOLTAGE TEMPERATURE DRIFT



MAX6071_25 OUTPUT VOLTAGE TEMPERATURE DRIFT



MAX6071_41 OUTPUT VOLTAGE TEMPERATURE DRIFT



MAX6071_25 LINE REGULATION



MAX6071_25 LOAD REGULATION



MAX6071_12 PSRR vs. FREQUENCY



MAX6071_25 PSRR vs. FREQUENCY



MAX6071_41 PSRR vs. FREQUENCY



MAX6071_12 SUPPLY CURRENT vs. INPUT VOLTAGE



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

MAX6071_25
SUPPLY CURRENT vs. INPUT VOLTAGE



MAX6071_41
SUPPLY CURRENT vs. INPUT VOLTAGE



MAX6071_12
ROUT vs. FREQUENCY



MAX6071_25
ROUT vs. FREQUENCY



MAX6071_41
ROUT vs. FREQUENCY



MAX6071_12
SUPPLY CURRENT vs. TEMPERATURE



MAX6071_25
SUPPLY CURRENT vs. TEMPERATURE



MAX6071_41
SUPPLY CURRENT vs. TEMPERATURE



MAX6070_12 OUTPUT NOISE
(0.1Hz TO 10Hz)



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

MAX6070_25 OUTPUT NOISE (0.1Hz TO 10Hz) (SOT23)



MAX6070_41 OUTPUT NOISE (0.1Hz TO 10Hz)



MAX6070_12 OUTPUT NOISE DENSITY vs. FREQUENCY



MAX6070_25 OUTPUT NOISE DENSITY vs. FREQUENCY



MAX6070_41 OUTPUT NOISE DENSITY vs. FREQUENCY



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

MAX6070_12 TURN-ON TRANSIENT (C_{FILTER} = 0µF)



MAX6070_25 TURN-ON TRANSIENT (C_{FILTER} = 0µF)



MAX6070_41 TURN-ON TRANSIENT (C_{FILTER} = 0µF)



MAX6070_12 TURN-ON TRANSIENT (C_{FILTER} = 0.1µF)



MAX6070_25 TURN-ON TRANSIENT (C_{FILTER} = 0.1µF)



MAX6070_41 TURN-ON TRANSIENT (C_{FILTER} = 0.1µF)



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

MAX6071_12 ±10mA LOAD TRANSIENT (C_{OUT} = 0.1µF)



MAX6071_25 ±10mA LOAD TRANSIENT (C_{OUT} = 0.1µF)



MAX6071_41 ±10mA LOAD TRANSIENT (C_{OUT} = 0.1µF)



MAX6070_12 LINE TRANSIENT (C_{OUT} = 0.1µF)



MAX6070_25 LINE TRANSIENT (C_{OUT} = 0.1µF)



MAX6070_41 LINE TRANSIENT (C_{OUT} = 0.1µF)



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

MAX6070_12 ENABLE TRANSIENT (C_{FILTER} = 0µF)



MAX6070_12 ENABLE TRANSIENT (C_{FILTER} = 0.1µF)



MAX6070_25 ENABLE TRANSIENT (C_{FILTER} = 0µF)



MAX6070_25 ENABLE TRANSIENT (C_{FILTER} = 0.1µF)



MAX6070_41 ENABLE TRANSIENT (C_{FILTER} = 0µF)



MAX6070_41 ENABLE TRANSIENT (C_{FILTER} = 0.1µF)



Pin Configurations



Pin Description

PIN		NAME	FUNCTION
MAX6070	MAX6071		
1	—	FILTER	Filter Input. Connect a 0.1µF capacitor from FILTER to ground to provide high-frequency bypass. Leave unconnected, if not used.
—	1	GNDF	Ground Force
2	—	GND	Ground
-	2	GNDS	Ground Sense. Connect to ground connection at the load.
3	3	EN	Enable. Drive high to enable the device. Drive low to disable the device.
4	4	IN	Supply Input
5	5	OUTS	Voltage Reference Sense Output
6	6	OUTF	Voltage Reference Force Output. Short OUTF to OUTS as close as possible to the load. Bypass OUTF with a capacitor (0.1µF to 10µF) to GND.

Bump Configuration



Bump Description

BUMP	NAME	FUNCTION
A1	EN	Enable. Drive high to enable the device. Drive low to disable the device.
A2	GNDS	Ground Sense. Connect to ground connection at the load.
A3	GNDF	Ground Force
B1	OUTS	Voltage Reference Sense Output
B2	OUTF	Voltage Reference Force Output. Short OUTF to OUTS as close as possible to the load. Bypass OUTF with a capacitor (0.1µF to 10µF) to GNDF.
B3	IN	Supply Input. Connect a 0.1µF capacitor to GNDF.

Detailed Description

Wideband Noise Reduction (FILTER)

To improve wideband noise and transient power-supply noise with the MAX6070, connect a 0.1µF capacitor from FILTER to GND (see the *Typical Operating Characteristics*). Larger values do not appreciably improve noise reduction. A 0.1µF capacitor reduces the spectral noise density at 1kHz from 60nV/√Hz to 30nV/√Hz for the 2.5V output. Noise at the input pin can affect output noise, but can be reduced by connecting an optional bypass capacitor between IN and GND as shown in Figure 1.

Output Bypassing

The MAX6070/MAX6071 require an output capacitor between 0.1µF and 10µF. Place the output capacitor as close to OUTF as possible. For applications driving switching capacitive loads or rapidly changing load currents, use a 0.1µF capacitor in parallel with a larger load capacitor to reduce equivalent series resistance (ESR). Larger capacitor values and lower ESR reduce transients on the reference output.

Supply Current

The MAX6070/MAX6071 draw 150µA of current and are virtually independent of the supply voltage, with only a 1.6µA/V variation with supply voltage.

Thermal Hysteresis

Thermal hysteresis is the change of output voltage at T_A = +25°C before and after the device is cycled over its entire operating temperature range. The typical thermal hysteresis value is 85ppm.

Turn-On Time

These devices typically turn on and settle to within 0.01% of their final value in 30µs. A noise reduction capacitor of 0.1µF increases the turn-on time of the MAX6070 to 10ms.

Output Force and Sense

The MAX6070/MAX6071 provide independent connections for the force output (OUTF) supplying current to the load and the circuit input regulating the load voltage through the output sense pin (OUTS). This configuration allows for the cancellation of the voltage drop on the lines connecting the MAX6070/MAX6071 and the load. When using the Kelvin connection made possible by the independent force and sense outputs, connect OUTF to the load and connect OUTS to OUTF at the point where the voltage accuracy is needed (see Figure 1). The MAX6071 features the same type of Kelvin connection to cancel drops in the ground return line. Connect the load to ground and connect GNDS to ground as close as possible to the load ground connection (see Figure 2).

Shutdown

The MAX6070/MAX6071 feature an active-high enable pin (EN). Pulling EN low disables the output with a resistive load to ground and forces the quiescent current to less than 1µA. The value of the load is typically 200kΩ. Pulling EN high enables normal operation.

Applications Information

Wideband Noise Reduction

Figure 1 shows a typical noise reduction filter application circuit. Note that the use of the wideband noise filter will increase turn-on time.

High-Resolution DAC and Reference from a Single Supply

Figure 2 shows a typical circuit providing the reference for a high-resolution, 16-bit MAX541 DAC.

Precision Current Source

Figure 3 shows a typical circuit providing a precision current source. The OUTF output provides the bias current for the bipolar transistor. OUTS and GNDS sense the voltage across the resistor and adjust the current sourced by OUTF accordingly.



Figure 1. Reference Output Kelvin Connection



Figure 2. Reference Ground Kelvin Connection



Figure 3. Precision Current Source

Long-Term Drift and Humidity Effects

There are many factors that contribute to a voltage reference's drift over time. These can include package stress, board stress and layout, humidity and part-to-part variation. In an effort to better quantify the drift of the MAX6070 core over time, Analog Devices has evaluated 16 samples on two identical bench setups. Sixteen MAX6070AAUT25+ samples were installed on a pair of development boards. One board was set up in a humidity and temperature controlled oven. The conditions were set to 25°C and 40% relative humidity. The second board was set up on the lab bench in the open air, where humidity was measured to fluctuate between 18% and 51%.

The results of these experiments are detailed in Figure 4, Figure 5, and Figure 6. The latest data shows the drift out to 5,800 hours. The y axis is the drift, measured in parts per million, between +50ppm and -50ppm. Figure 4 shows the 16 parts on the lab bench in the open air. It is here the effects of the humidity fluctuating between 18% and 51% can be seen.

Figure 5 details the same set up in the humidity controlled oven. Temperature (25°C) and humidity (40%) are relatively consistent inside the oven. Data was affected a bit at about the 2,500 hour mark when the pump that regulates the humidity temporarily stopped working for about 48 hours. This caused a brief spike in the output voltages before they returned to their previous profile.

Figure 6 shows the results of temperature and humidity measurements both inside and outside the oven. The key parameter to note is the purple line which represents the humidity outside the oven (on the lab bench). The swings in humidity are apparent in Figure 4, with the output voltage drift primarily tracking the humidity changes.

Analog Devices is studying the effects of drift and humidity on multiple references beyond 1,000 hours. Contact the Analog Devices technical support line or your local sales office for details on the latest data.



Figure 4. MAX6070AAUT2.5+ Long-Term Drift on the Bench Setup



Figure 5. MAX6070AAUT25+ Long-Term Drift in the Oven (Temperature = +25°C, Relative Humidity = 40%)



Figure 6. Temperature and Relative Humidity Measured Inside the Oven and in the Lab Benchtop Environment

Selector Guide

PART	FILTER	V_{OUT} (V)	ACCURACY (%)	TOP MARK
MAX6070AAUT12+T	Yes	1.25	0.04	+ACPF
MAX6070AAUT18/V+T	Yes	1.8	0.04	+ACVV
MAX6070AAUT18+T	Yes	1.8	0.04	+ACPH
MAX6070AAUT21+T	Yes	2.048	0.04	+ACPJ
MAX6070AAUT25+T	Yes	2.5	0.04	+ACPL
MAX6070AAUT30+T	Yes	3.0	0.04	+ACPN
MAX6070AAUT33+T	Yes	3.3	0.04	+ACPP
MAX6070AAUT33/V+T	Yes	3.3	0.04	+ACVN
MAX6070AAUT41+T	Yes	4.096	0.04	+ACPR
MAX6070AAUT50+T	Yes	5.0	0.04	+ACPV
MAX6070AAUT50/V+T	Yes	5.0	0.04	+ACTR
MAX6070BAUT12+T	Yes	1.25	0.08	+ACPG
MAX6070BAUT12/V+T	Yes	1.25	0.08	+ACSP
MAX6070BAUT18+T	Yes	1.8	0.08	+ACPI
MAX6070BAUT21+T	Yes	2.048	0.08	+ACPK
MAX6070BAUT21/V+T	Yes	2.048	0.08	+ACVG
MAX6070BAUT25+T	Yes	2.5	0.08	+ACPM
MAX6070BAUT25/V+T	Yes	2.5	0.08	+ACTS
MAX6070BAUT30+T	Yes	3.0	0.08	+ACPO
MAX6070BAUT30/V+T	Yes	3.0	0.08	+ACWU
MAX6071AAUT30/V+T	No	3.0	0.04	+ACVQ
MAX6070BAUT33+T	Yes	3.3	0.08	+ACPQ
MAX6070BAUT33/V+T	Yes	3.3	0.08	+ACUY
MAX6070BAUT41+T	Yes	4.096	0.08	+ACPS
MAX6070BAUT41/V+T	Yes	4.096	0.08	+ACTT
MAX6070DAUT12/V+T	Yes	1.25	0.2	+ACWG
MAX6070DAUT25/V+T	Yes	2.5	0.2	+ACWF
MAX6070DAUT30/V+T	Yes	3.0	0.2	+ACWE
MAX6070DAUT41/V+T	Yes	4.096	0.2	+ACWC
MAX6070BAUT50+T	Yes	5.0	0.08	+ACPW
MAX6070BAUT50/V+T	Yes	5.0	0.08	+ACVA
MAX6071AAUT12+T	No	1.25	0.04	+ACPX
MAX6071AAUT18+T	No	1.8	0.04	+ACPZ
MAX6071AAUT21+T	No	2.048	0.04	+ACQB
MAX6071AAUT25+T	No	2.5	0.04	+ACQD
MAX6071AAUT30+T	No	3.0	0.04	+ACQF
MAX6071AAUT33+T	No	3.3	0.04	+ACQH
MAX6071AAUT41+T	No	4.096	0.04	+ACQJ
MAX6071AAUT50+T	No	5.0	0.04	+ACQN
MAX6071BAUT12+T	No	1.25	0.08	+ACPY
MAX6071BAUT18+T	No	1.8	0.08	+ACQA
MAX6071BAUT21+T	No	2.048	0.08	+ACQC
MAX6071BAUT25+T	No	2.5	0.08	+ACQE

Selector Guide (continued)

PART	FILTER	V_{OUT} (V)	ACCURACY (%)	TOP MARK
MAX6071ANT25+T	No	2.5	0.1	+F
MAX6071BAUT25/V+T	No	2.5	0.08	+ACTU
MAX6071BAUT30+T	No	3.0	0.08	+ACQG
MAX6071BAUT33+T	No	3.3	0.08	+ACQI
MAX6071BAUT41+T	No	4.096	0.08	+ACQK
MAX6071BAUT50+T	No	5.0	0.08	+ACQO

/V denotes an automotive qualified part.
+Denotes a lead(Pb)-free/RoHS-compliant package.
T = Tape and reel.

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE
MAX6070AAUT18/V+T	-40°C to +125°C	6 SOT23
MAX6070_AUT_ _+T	-40°C to +125°C	6 SOT23
MAX6070AAUT33/V+T	-40°C to +125°C	6 SOT23
MAX6070AAUT50/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT12/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT21/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT25/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT30/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT33/V+T	-40°C to +125°C	6 SOT23
MAX6070BAUT41/V+T	-40°C to +125°C	6 SOT23
MAX6070DAUT12/V+T	-40°C to +125°C	6 SOT23
MAX6070DAUT25/V+T	-40°C to +125°C	6 SOT23
MAX6070DAUT30/V+T	-40°C to +125°C	6 SOT23
MAX6070DAUT41/V+T	-40°C to +125°C	6 SOT23
MAX6071_AUT_ _+T	-40°C to +125°C	6 SOT23
MAX6071ANT25+T	-40°C to +125°C	6 WLP
MAX6071AAUT30/V+T	-40°C to +125°C	6 SOT23
MAX6071BAUT25/V+T	-40°C to +125°C	6 SOT23

+Denotes a lead(Pb)-free/RoHS-compliant package.
T = Tape and reel.

Note: The MAX6070/MAX6071 are available in A, B, or D grade with various output voltages. Choose the desired grade and output voltage from the Selector Guide and insert the suffix in the blank above to complete the part number.

Chip Information

PROCESS: BIPOLAR

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	10/12	Initial release	—
1	1/13	Added 2.048V, 3.0V, and 5.0V options to data sheet. Revised General Description, *Benefits and Features*, *Absolute Maximum Ratings, Electrical Characteristics*, and *Selector Guide*	1–9, 17, 18
2	3/13	Added 1.8V and 3.3V options to data sheet. Revised *General Description, Benefits and Features, Electrical Characteristics,* and *Selector Guide*	1, 2–12, 21, 22
3	2/14	Added automotive package for the MAX6070B.	21
4	7/15	Added automotive packages to data sheet and revised TOC9b. Revised *Benefits and Features* section.	1, 16, 22, 23
5	1/16	Added WLP option text, associated *Electrical Characteristics* table, package drawing and *Bump Description* table	1, 2, 7, 19, 22
6	12/17	Added AEC statement to *Benefits and Features* section and updated *Selector Guide*	1, 23
7	3/18	Updated *Selector Guide* and *Ordering Information* tables	23, 24
8	8/18	Updated *Selector Guide* and *Ordering Information* tables	23, 24
9	9/18	Updated *Selector Guide* and *Ordering Information* tables	23, 24
10	1018	Updated *Applications Information*, *Packaging Information*, *Electrical Characteristics* table, *Selector Guide*, and *Ordering Information*	1, 2–12, 23, 24
11	12/18	Updated *Selector Guide* and *Ordering Information*	23, 24
12	3/19	Updated *Package Information, Detailed Description, Selector Guide*, and *Ordering Information*	2, 22–24
13	5/19	Updated *Package Information*	2
14	7/19	Updated *Ordering Information and Selector Guide*	24, 25
15	11/19	Updated *Electrical Characteristics, Selector Guide*, and *Ordering Information*	10, 24, 25
16	4/20	Added (max, A grade) in the *General Description and Benefits and Features* sections, updated *Electrical Characteristics* table, added future part and deleted asterisk in the *Selector Guide* and *Ordering Information tables*	1, 3, 6, 8–10, 24, 25
17	6/20	Updated *Ordering Information* and *Selector Guide*	25
18	12/20	Updated *Selector Guide* and *Ordering Information*	24, 25
19	9/24	Updated *Selector Guide* and *Ordering Information*	24, 25

ANALOG DEVICES

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners. All Analog Devices products contained herein are subject to release and availability.