WTQB1000N

Product no.: WTQB1000N



Benefits

- Precise, camera-assisted component placement
- Suitable for even the smallest components, starting at 1.0 mm and up
- Performs the entire rework process
- Flexible magnetic anchoring system
- Very easy and convenient for manual use
- Software-controlled rework cycle
- Unparalleled price / performance ratio
- Full range of tools and accessories
- Exact replication of results, time after time
- No visual calibration required

Technical Data

Dimensions L x W x H (inches)	25,98 x 14,17 x 15,35
Dimensions L x W x H (mm)	660 x 360 x 390
Space requirement/workspace L x W x H (Inches)	31,5 x 19,7 x 15,7
Space requirement/workspace L x W x H (mm)	800 x 500 x 400
Recommended assembly size (mm)	---
Recommended component size (mm)	---
Compressed air connection	Air hose 6 mm (0,24“)
Compressed air connection accessory	dry, oil free
Compressed air supply kPa/bar	550 - 800 / 5,5 - 8,0
Air consumption l/min	35 - 85
Max. hot air flow rate l/min	6 - 35
ESD-safe	on
Noise level (distance 1 m) dB(A)	---
Weight (approx.) in kg	22
Power consumption	2644 VA
Rated output of top heating (W)	300
Rated output of bottom heating (W)	2000
Protection class	1
Voltage	110 V
Temperature range of top heating (°C)	---
Temperature range of bottom heating (°C)	1 - 200
Optical positioning	on
Positioning aid	Optical positioning frame
Temperature accuracy of top heating	tbd
Temperature accuracy of bottom heating	tbd
Thermocouple connection	2 x Type-K

Weller Tools GmbH
Carl-Benz-Straße 2
74354 Besigheim
Germany

Phone: +49 (0) 7143 / 580-0
Fax.: +49 (0) 7143 / 580-108
Email: info@weller-tools.com
Web: www.weller-tools.com