SMD Switching Diode

CDSUR4148

RoHS Device



Features

-High Speed

-Designed for mounting on small surface.

-Extremely thin/leadless package.

-High mounting capability, strong surge withstand, high reliability.



Mechanical data

-Case: 0603/SOD-523F standard package, molded plastic.

-Terminals: Gold plated, solderable per MIL-STD-750, method 2026.

-Polarity: Indicated by cathode band.

-Mounting position: Any.

-Weight: 0.003 gram (approx.).

Maximum Rating (at T_A=25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Repetitive peak reverse voltage		V_{RRM}			100	V
Reverse voltage		V_R			75	V
Average forward current		I_O			150	mA
Forward current,surge peak	T_P = 1uS T_P = 1mS	I_{FSM}		4 1		A
Repetitive peak forward current		I_{FRM}			300	mA
Power Dissipation		P_D			150	mW
Storage temperature		T_{STG}	-40		+125	°C
Junction temperature		T_j			+125	°C

Electrical Characteristics (at T_A=25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	I_F = 50 mA DC	V_F			1.0	V
Reverse current	V_R = 20 V V_R = 75 V	I_R			25 2.5	nA uA
Capacitance between terminals	f = 1 MHz,and 0VDC reverse voltage	C_T			4	pF
Reverse recovery time	I_F = I_R= 10 mA, R_L =100 ohms, I_{rr} = 1mA	T_{rr}			4	nS

RATING AND CHARACTERISTIC CURVES (CDSUR4148)

Fig. 1 - Forward characteristics



Fig. 2 - Reverse characteristics



Fig. 3 - Capacitance between terminals characteristics



Fig. 4 - Current derating curve



Reel Taping Specification



	SYMBOL	A	B	C	d	D	D_1	D_2
0603 (SOD-523F)	(mm)	1.00 ± 0.10	1.85 ± 0.10	1.00 ± 0.10	1.55 ± 0.05	178 ± 1	60.0 MIN.	13.0 ± 0.20
	(inch)	0.039 ± 0.004	0.073 ± 0.004	0.039± 0.004	0.061 ± 0.002	7.008 ± 0.04	2.362 MIN.	0.512 ± 0.008

	SYMBOL	E	F	P	P_0	P_1	T	W	W_1
0603 (SOD-523F)	(mm)	1.75 ± 0.10	3.50 ± 0.05	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	0.23 ± 0.05	8.00 ± 0.20	13.5 MAX.
	(inch)	0.069 ± 0.004	0.138 ± 0.002	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.009 ± 0.002	0.315 ± 0.008	0.531 MAX.

Suggested PAD Layout

SIZE	0603/SOD-523F	
	(mm)	(inch)
A	1.25	0.049
B	0.60	0.024
C	1.00	0.039
D	1.85	0.073
E	0.65	0.026



Standard Package

Case Type	Qty per Reel	Reel Size
	(Pcs)	(inch)
0603/SOD-523F	4000	7