CUI INC
a bel group

SERIES: PCN1-M | DESCRIPTION: DC-DC CONVERTER

FEATURES

- up to 1 W isolated output
- industry standard surface mount package
- nominal input voltages: 5, 12 Vdc
- single/dual unregulated output
- 1,500 Vdc isolation voltage
- low ripple and noise
- -40 to 100°C
- efficiency up to 81%
- meets EN 62368-1



RoHS

MODEL

MODEL	input voltage typ (Vdc)	input voltage range (Vdc)	output voltage (Vdc)	output current min (mA)	output current max (mA)	output power max (W)	ripple & noise[1] max (mVp-p)	efficiency typ (%)
PCN1-S5-S5-M	5	4.5~5.5	5	0	200	1	75	79
PCN1-S5-S12-M	5	4.5~5.5	12	0	84	1	75	79
PCN1-S5-S15-M	5	4.5~5.5	15	0	67	1	75	79
PCN1-S5-D5-M	5	4.5~5.5	±5	0	±100	1	75	74
PCN1-S5-D12-M	5	4.5~5.5	±12	0	±42	1	75	78
PCN1-S5-D15-M	5	4.5~5.5	±15	0	±33	1	75	78
PCN1-S12-S5-M	12	10.8~13.2	5	0	200	1	75	80
PCN1-S12-S12-M	12	10.8~13.2	12	0	84	1	75	81
PCN1-S12-S15-M	12	10.8~13.2	15	0	67	1	75	81
PCN1-S12-D5-M	12	10.8~13.2	±5	0	±100	1	75	77
PCN1-S12-D12-M	12	10.8~13.2	±12	0	±42	1	75	80
PCN1-S12-D15-M	12	10.8~13.2	±15	0	±33	1	75	81

Notes:
1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with a 0.33 µF ceramic capacitor on the output.
2. Required to add a 2.2 µF ceramic capacitor to the input to reduce input voltage stress.
3. All specifications are measured at Ta=25°C, nominal input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	5 Vdc input models 12 Vdc input models	4.5 10.8	5 12	5.5 13.2	Vdc Vdc
surge voltage	for maximum of 100 ms 5 Vdc input models 12 Vdc input models			 9 18	 Vdc Vdc
current	5 Vdc input models 12 Vdc input models		250 110		mA mA
filter	capacitive				
input reverse polarity protection	no				
input fuse	0.5 A time delay fuse for all models (recommended)				

Notes: 1. Required to add a 2.2 µF ceramic capacitor to the input to reduce input voltage stress.

OUTPUT

parameter	conditions/description	min	typ	max	units
maximum capacitive load	single output models dual output models			220 100	µF µF
voltage accuracy				±3.0	%
line regulation	1.0% change in input voltage			±1.2	%
load regulation	from 20% load to full load			±10	%
switching frequency	at nominal Vin, full load		100		kHz
temperature coefficient				±0.05	%/°C

PROTECTIONS

parameter	conditions/description	min	typ	max	units
short circuit protection	momentary			1	s

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output for 1 minute	1,500			Vdc
isolation resistance	input to output	1,000			MΩ
isolation capacitance	input to output		10		pF
safety approvals	meets 62368: EN				
conducted emissions	EN 55022 Class B (external circuit required, see Figure 4)				
MTBF	as per MIL-HDBK-217F, full load, GB, 25°C		1,500,000		hours
RoHS	2011/65/EU				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40		100	°C
storage temperature		-55		125	°C
operating humidity	non-condensing			95	%

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reflow soldering	see reflow solder profile			245	°C

Notes:
1. Soldering paste: SHENMAO PF610-P (Sn/Ag/Cu)
2. Ramp up rate during preheat: 1.79°C/second (from 30°C~155°C)
3. Soaking temperature: 0.33°C/second (from 155°C~185°C)
4. Ramp up rate during reflow: 0.71°C/second (from 220°C~245°C)
5. Peak temperature: 245°C (10 seconds max), above 220°C 40 to 70 seconds
6. Ramp up rate during cooling: -1.75°C/second (from 220°C~150)



MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	single output models: 0.54 x 0.36 x 0.29 [13.7 x 9.2 x 7.4 mm] dual output models: 0.64 x 0.36 x 0.29 [16.2 x 9.2 x 7.4 mm]				inches inches
case material	non-conductive black plastic				
weight	single output models dual output models		1.4 1.5		g g

MECHANICAL DRAWING

Single output models
units: inches [mm]
tolerance: X.XX ±0.01 [±0.25]
X.XXX ±0.005 [±0.13]
pin section tolerance: ±0.002[±0.05]



PIN CONNECTIONS	
PIN	Function
	Single
1	-Vin
2	+Vin
3	No pin
4	-Vout
5	+Vout
6	No pin
7	No pin
8	NC

NC=no connection



Recommended PCB Layout
Top View





MECHANICAL DRAWING (CONTINUED)

Dual output models
units: inches [mm]
tolerance: X.XX ±0.01 [±0.25]
X.XXX ±0.005 [±0.13]
pin section tolerance: ±0.002[±0.05]

PIN CONNECTIONS	
PIN	Function
	Dual
1	-Vin
2	+Vin
3	No pin
4	Common
5	-Vout
6	No pin
7	+Vout
8	No pin
9	No pin
10	NC

NC=no connection









DERATING CURVE



EFFICIENCY CURVES













EFFICIENCY CURVES (CONTINUED)

EFFICIENCY VS OUTPUT LOAD
PCN1-S12-S5-M



EFFICIENCY VS OUTPUT LOAD
PCN1-S12-S12-M



EFFICIENCY VS OUTPUT LOAD
PCN1-S12-S15-M



EFFICIENCY VS OUTPUT LOAD
PCN1-S12-D5-M



EFFICIENCY VS OUTPUT LOAD
PCN1-S12-D12-M



EFFICIENCY VS OUTPUT LOAD
PCN1-S12-D15-M



PACKAGING (TUBE)

units: mm

Tube Size: 14 x 14 x 535 mm
Single Output Models QTY: 36 pcs per tube
Dual Output Models QTY: 30 pcs per tube



PACKAGING (TAPE & REEL)

Single output models

units: mm

Reel Size: Ø13”
QTY: 430 pcs per reel



Dual output models

units: mm

Reel Size: Ø13”
QTY: 430 pcs per reel



TEST CONFIGURATIONS

Input Ripple Current & Output Noise

Figure 1
Measuring Input Ripple Current



Figure 2
Measuring Output Ripple & Noise for Single Output Models



Figure 3
Measuring Output Ripple & Noise for Dual Output Models



Table 1

L1	12 µH
C1	2.2 µF tantalum capacitor
C2	NC

Table 2

Input Voltage (Vdc)	Cin
5	2.2 µF ceramic capacitor
12	2.2 µF ceramic capacitor

EMC RECOMMENDED CIRCUIT

Test Condition
Input Voltage: Nominal
Output Load: Full Load

Figure 4
Conducted Emissions Test Circuit



Table 3

EN55022 Class B Recommended External Circuit Components			
Input Voltage (Vdc)	C1[1]	C2[1]	L1
5	4.7 µF / 25 V	4.7 µF / 25 V	10 µH
12	4.7 µF / 25 V	4.7 µF / 25 V	10 µH

Notes: 1. Ceramic Capacitor

REVISION HISTORY

rev.	description	date
1.0	initial release	07/26/2016
1.01	added tube packaging option	06/09/2017
1.02	removed tube packaging option	02/14/2020
1.03	safeties updated	05/26/2021
1.04	derating curve, efficiency curves and circuit figures updated	07/01/2021
1.05	CE certification updated	11/03/2022

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC
a bel group

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.