STATICO

Product Specifications for S1010 Series Metal Wrist Grounding Strap





Description

The S1010 Series is available in a 6' Coil Cord, 4mm (1/8") Snap. This Wrist Strap & Coil Cord meets ANSI/ESD Standard S1.1 & ANSI/ESD S20.20.

Specifications

A. Metal Band

- **Each link is individually coated with a non-stretchable insulative coating.**
- **The material beneath the coating is non-magnetic Stainless Steel.**

Number of Links per Size:

• **Small**	**31+2**	**for Wrists from 4.5"-to-6-1/4" (114mm-to-152mm)**
• **Medium**	**37+2**	**for Wrists from 5.5"-to-7.25" (140mm-to-184mm)**
• **Large**	**41+2**	**for Wrists larger than 6.5" (165mm)**
• **Extra Large**	**43+2**	**for X-Large Wrists**

B. Coil Cord

• **Conductor**	**7-Strand single tinsel wire**
• **Jacket Insulation**	**90 Shore A Polyurethane**
• **Wire Diameter**	**0.09"**
• **Coil Diameter**	**0.04" + 0.02"**
• **Cable Break Load**	**< 28 lbs.**
• **Pull Force (Molded Plug End)**	**< 25 lbs.**
• **Bending Test**	**>36,000 Cycles**
2,000 Bending Cycle/Hour	
500g Load Weight	**>120°**