Dialight

655 Series
½" Snap-in Panel Mount Indicators



Certifications & Ratings

- RoHS compliant

Application

The 655 Series LED Panel Mount Indicators are designed for a variety of applications such as.


- Main power indication
- Remote power indication
- Status indication
- Maintenance and warning indication
- Instrumentation

. . . and many more!


Dimensions

inches [mm]

Flat Lens



Domed Lens



Mechanical Information

Mounting Hole Size:	0.50" (12.7 mm)
Max Panel Thickness:	0.138" (3.5 mm) (Domed Lens); 0.216" (5.5 mm) (Flat Lens)

Specifications

Voltage Options:	12 & 24 VDC and 120 & 230 VAC (Flat Lens only), no resistor required
Operating temp:	-20 °C to +85 °C (-4 °F to +185 °F)
Storage Temp:	-20 °C to +85 °C (-4 °F to +185 °F)
Electrical Connection:	250 Faston quick connect terminals (Flat Lens only) or wire leads
Housing:	Polycarbonate
Terminals:	Brass—Nickel Plated (Flat Lens only)
Wire Leads:	18 AWG (Flat Lens), 26 AWG (Domed Lens)

RoHS COMPLIANT

Dialight

Ordering Information 655 Series

Dialight P/N		Color	Voltage (VDC)	Current (mA)	Typical Intensity (mcd)
Wire Leads	Solder Terminals				
Flat Lens					
655-1103-103F	655-1103-104F	Red	12	20	270
655-1203-103F	655-1203-104F	Green			700
655-1303-103F	655-1303-104F	Yellow			200
655-1403-103F	655-1403-104F	Blue			100
655-1104-103F	655-1104-104F	Red	24		270
655-1204-103F	655-1204-104F	Green			700
655-1304-103F	655-1304-104F	Yellow			200
655-1404-103F	655-1404-104F	Blue			100
Domed Lens					
655-2103-103F	NA	Red	12	20	3000
655-2203-103F	NA	Green			2500
655-2303-103F	NA	Yellow			1500
655-2403-103F	NA	Blue			700
655-2104-103F	NA	Red	24		3000
655-2204-103F	NA	Green			2500
655-2304-103F	NA	Yellow			1500
655-2404-103F	NA	Blue			700

Part Number Guide

RoHS Compliant

6 5 5 - X X X X - 1 0 X F

Lens Style
- Flat: 1
- Domed: 2

Color
- Red: 1 0
- Green: 2 0
- Yellow: 3 0
- Blue: 4 0

Voltage
- 3: 12 VDC
- 4: 24 VDC
- 5: 120 VAC
- 9: 230 VAC

(Flat Lens only)

Termination
- 3: Wire Leads
- 4: Solder Terminals

(Flat Lens only)

Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com

Warranty Statement: Except for the warranty expressly provided for [herein/above/below], Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.