Specifications

Photo is representative

Eaton S811+N66P3S-MA

Eaton S811+ soft starter, with Digital Interface Module, 66 A, N-frame, Premium, 600 V rated, Level/Edge Sense, 3P, 24 V power, 200-600 V operating voltage, 47-63 Hz, 1-2 conductors, #22-14 AWG wire, 120 Vdc, 240 Vac

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+N66P3S-MA
UPC	786689326975
PRODUCT LENGTH/DEPTH	6.45 in
PRODUCT HEIGHT	7.37 in
PRODUCT WIDTH	2.66 in
PRODUCT WEIGHT	5.8 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	IEC 947 CSA Certified CSA Certified for Elevator Duty ABS Certified EN 60947-4-2
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specification

AMPERAGE RATING	66A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240 V
DC CURRENT - MAX	120 V
NUMBER OF POLES	Three
TYPE	Soft s
FREQUENCY RATING	47-63
POWER SUPPLY	24 V
FRAME SIZE	N
OPTIONS	Pump contr exten ramp 600V Prem Inline inside delta confi Level sense
OPERATING TEMPERATURE - MAX	50 °C
COMMUNICATION	Modb RTU
NEMA RATING	NEM
SIZE	NEM
OPERATING VOLTAGE	200-6
MODULE INTERFACE	Digit interf modu
OPERATING TEMPERATURE - MIN	-30 °C