Specifications

Photo is representative

Eaton S811+R13N3S-MA

Eaton S811+ soft starter, 135 A, R-frame, Three-pole, 24 V power, 200-600 V operating voltage, 47-63 Hz, 1-2 conductors, # 14-4/0 AWG wire, 120 Vdc, 240 Vac, Modbus RTU, NEMA 0, LCD display, -30°C to -50°C

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+R13N3S-MA
UPC	786689327002
PRODUCT LENGTH/DEPTH	6.64 in
PRODUCT HEIGHT	7.92 in
PRODUCT WIDTH	4.38 in
PRODUCT WEIGHT	10.5 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified EN 60947-4-2 IEC 947 CSA Certified for Elevator Duty ABS Certified
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specification

AMPERAGE RATING	135A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240 V
DC CURRENT - MAX	120 V
NUMBER OF POLES	Three pole
TYPE	Soft starte
FREQUENCY RATING	47-63 Hz
POWER SUPPLY	24 V
FRAME SIZE	R
OPERATING TEMPERATURE - MAX	50 °C
COMMUNICATION	Modb RTU
NEMA RATING	NEM 0
SIZE	NEM 0
OPERATING VOLTAGE	200-6 V
MODULE INTERFACE	Digit interf modu
OPERATING TEMPERATURE - MIN	-30 °