Specifications

Photo is representative

Eaton S811+T18N3S-MA

Eaton S811+ soft starter, 180 A, T-frame, Three-pole, 24 V power, 200-600 V operating voltage, 47-63 Hz, 1-2 conductors, #4 AWG to 500 kcmil wire, 120 Vdc, 240 Vac, Modbus RTU, NEMA 0, LCD display, -30°C to -50°C

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+T18N3S-MA
UPC	786689327026
PRODUCT LENGTH/DEPTH	6.47 in
PRODUCT HEIGHT	12.71 in
PRODUCT WIDTH	7.65 in
PRODUCT WEIGHT	48 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified IEC 947 ABS Certified CSA Certified for Elevator Duty EN 60947-4-2
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specification

AMPERAGE RATING	180A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240 V
DC CURRENT - MAX	120 V
NUMBER OF POLES	Three pole
TYPE	Soft starte
FREQUENCY RATING	47-63 Hz
POWER SUPPLY	24 V
FRAME SIZE	T
OPERATING TEMPERATURE - MAX	50 °C
COMMUNICATION	Modb RTU
NEMA RATING	NEM 0
SIZE	NEM 0
OPERATING VOLTAGE	200-6 V
MODULE INTERFACE	Digit interf modu
OPERATING TEMPERATURE - MIN	-30 °