Specifications

Photo is representative

Eaton S811+T18P3S-MA

Eaton S811+ soft starter, 180 A, T-frame, Premium, 600 V rated, Level/Edge Sense, Three-pole, 47-63 Hz, 1-2 conductors, #3 AWG to 500 kcmil wire, 120 Vdc, 240 Vac, Modbus RTU, NEMA 0, LCD display, -30°C to -50°C, 24 V power

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+T18P3S-MA
UPC	786689327033
PRODUCT LENGTH/DEPTH	6.47 in
PRODUCT HEIGHT	12.71 in
PRODUCT WIDTH	7.65 in
PRODUCT WEIGHT	48 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ABS Certified IEC 947 CSA Certified for Elevator Duty CSA Certified EN 60947-4-2
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specifications

AMPERAGE RATING	180A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240 V
DC CURRENT - MAX	120 V
NUMBER OF POLES	Three
TYPE	Soft s
FREQUENCY RATING	47-63
POWER SUPPLY	24 V
FRAME SIZE	T
OPTIONS	Inline inside delta config Pump contro exten ramp Premi Level sense 600V
OPERATING TEMPERATURE - MAX	50 °C
COMMUNICATION	Modb RTU
NEMA RATING	NEM
SIZE	NEM
OPERATING VOLTAGE	200-6
MODULE INTERFACE	Digita interf modu
OPERATING TEMPERATURE - MIN	-30 °C