Specifications

Photo is representative

Eaton S811+U36P3S-MA

Eaton S811+ soft starter, Frame U, 360 A, 300 hp, 480 V, 112-360 FLA, 24 Vdc, 200-600 V operating, #4 AWG to 500 kcmil, 2 conductors, LCD, Inline or inside-the-delta wiring configuration, Premium 600 V, HLD circuit breaker

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+U36P3S-MA
UPC	786689326531
PRODUCT LENGTH/DEPTH	7.16 in
PRODUCT HEIGHT	12.72 in
PRODUCT WIDTH	7.73 in
PRODUCT WEIGHT	48 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified for Elevator Duty ABS Certified EN 60947-4-2 IEC 947 CSA Certified
CATALOG NOTES	S811+T_, S811+U_ and S811+V_ units require lug kits found on Page V6-T1-89, , level/edge sense, pump control and extended ramp

Product specification

AMPERAGE RATING	360A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240 V
DC CURRENT - MAX	120 V
NUMBER OF POLES	Three pole
TYPE	Soft starte
FREQUENCY RATING	47-63 Hz
POWER SUPPLY	24 V
FRAME SIZE	U
OPTIONS	Prem 600V
COMMUNICATION	Modb RTU
NEMA RATING	NEM 0
SIZE	NEM 0
OPERATING VOLTAGE	200-6 V
MODULE INTERFACE	Digit interf modu