Specifications

Photo is representative

Eaton S811+U50N3S-MA

Eaton S811+ soft starter, Frame U, 500 A, 400 hp, 480 V, 24 Vdc, 200-600 V operating, #4 AWG to 500 kcmil, 1-2 conductors, LCD, HLD circuit breaker, Class RK5/J Fuse, 156-500 FLA

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+U50N3S-MA
UPC	786689326593
PRODUCT LENGTH/DEPTH	7.16 in
PRODUCT HEIGHT	12.72 in
PRODUCT WIDTH	7.73 in
PRODUCT WEIGHT	48 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified IEC 947 EN 60947-4-2 ABS Certified CSA Certified for Elevator Duty
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specification

AMPERAGE RATING	500A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240
DC CURRENT - MAX	120
NUMBER OF POLES	Thre pole
TYPE	Soft starte
FREQUENCY RATING	47-6 Hz
POWER SUPPLY	24 V
FRAME SIZE	U
COMMUNICATION	Mod RTU
NEMA RATING	NEM 0
SIZE	NEM 0
OPERATING VOLTAGE	200- V
MODULE INTERFACE	Digit inter modu