Specifications

Photo is representative

Eaton S811+V42N3S-MA

Eaton S811+ soft starter, 420 A, V-frame, Three-pole, 24 V power, 200-600 V operating voltage, 47-63 Hz, 1-2 conductors, #2/0 AWG to 500 kcmil wire, 120 Vdc, 240 Vac, Modbus RTU, NEMA 0, LCD display, -30°C to -50°C

General specifications

PRODUCT NAME	Eaton S811+ soft starter
CATALOG NUMBER	S811+V42N3S-MA
UPC	786689326661
PRODUCT LENGTH/DEPTH	7.39 in
PRODUCT HEIGHT	16.57 in
PRODUCT WIDTH	11.05 in
PRODUCT WEIGHT	103 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified CSA Certified for Elevator Duty EN 60947-4-2 ABS Certified IEC 947
CATALOG NOTES	All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Product specification

AMPERAGE RATING	420A
DISPLAY MATERIAL	LCD
AC CURRENT - MAX	240
DC CURRENT - MAX	120
NUMBER OF POLES	Thre pole
TYPE	Soft starte
FREQUENCY RATING	47-6 Hz
POWER SUPPLY	24 V
FRAME SIZE	V
COMMUNICATION	Mod RTU
NEMA RATING	NEM 0
SIZE	NEM 0
OPERATING VOLTAGE	200- V
MODULE INTERFACE	Digit inter modu

Powering Business Worldwide