RU2AM - RU2M

FAST RECOVERY RECTIFIER DIODES

PRV : 400 - 600 Volts
Io : 1.1 Ampere

FEATURES :

* High current capability
* High surge current capability
* High reliability
* Low reverse current
* Low forward voltage drop
* Fast switching for high efficiency
* Pb / RoHS Free

MECHANICAL DATA :

* Case : D2 Molded plastic
* Epoxy : UL94V-O rate flame retardant
* Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
* Polarity : Color band denotes cathode end
* Mounting position : Any
* Weight : 0.465 gram

D2



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

RATING	SYMBOL	RU2M	RU2AM	UNIT
Maximum Peak Reverse Voltage	V_{RM}	400	600	V
Maximum Peak Reverse Surge Voltage	V_{RSM}	450	650	V
Maximum Average Forward Current Ta = 50 °C	$I_{F(AV)}$	1.1		A
Maximum Peak Forward Surge Current (50 Hz, Half-cycle, Sine wave, Single Shot)	I_{FSM}	20		A
Maximum Forward Voltage at I_F = 1.1 A	V_F	1.2		V
Maximum Reverse Current at $V_R = V_{RM}$ Ta = 25 °C	I_R	10		µA
Maximum Reverse Current at $V_R = V_{RM}$ Ta = 100 °C	$I_{R(H)}$	300		µA
Maximum Reverse Recovery Time (Note 1)	Trr	400		ns
Junction Temperature Range	T_J	- 40 to + 150		°C
Storage Temperature Range	T_{STG}	- 40 to + 150		°C

Note :

(1) Reverse Recovery Test Conditions : I_F = 10 mA, I_{RP} = 10 mA.

RATING AND CHARACTERISTIC CURVES (RU2AM - RU2M)

FIG.1 - REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



NOTE : $I_F = I_{RP}$ = 10 mA TO 1 mA

FIG.2 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT



FIG.3 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



FIG.4 - TYPICAL FORWARD CHARACTERISTICS



FIG.5 - TYPICAL REVERSE CHARACTERISTICS

