EPCOS

SAW Components

Data Sheet M 9260 M



Data Sheet

Standard

Plastic package **SIP5K**

- M/N



Dimensions in mm, approx. weight 1,0 g

Features

- TV IF audio filter with pass bands for picture carrier at 45,75 MHz and sound carrier at 41,25 MHz

Terminals

- Tinned CuFe alloy

Pin configuration

1	Input
2	Input - ground
3	Chip carrier - ground
4	Output
5	Output



Type	Ordering code	Marking and package according to	Packing according to
M 9260 M	B39458-M9260-M100	C61157-A1-A15	F61074-V8067-Z000

Maximum ratings

Operable temperature range	T_A	–25/+65	˚C	
Storage temperature range	T_{stg}	–40/+85	˚C	
DC voltage	V_{DC}	5	V	between any terminals
AC voltage	V_{pp}	10	V	between any terminals

Characteristics

Reference temperature: T_A = 25 °C
Terminating source impedance: Z_S = 50 Ω
Terminating load impedance: Z_L = 2 kΩ || 3 pF

			min.	typ.	max.	
Insertion attenuation		α				
Reference level for the following data	41,25 MHz		12,6	14,1	15,6	dB
Relative attenuation		α_{rel}				
Picture carrier	45,75 MHz		–0,6	0,4	1,4	dB
Color carrier	42,17 MHz		22,0	28,0	—	dB
Adjacent picture carrier	39,75 MHz		42,0	50,0	—	dB
Adjacent sound carrier	47,25 MHz		40,0	48,0	—	dB
Lower sidelobe	35,00 ... 39,75 MHz		40,0	46,0	—	dB
Upper sidelobe	47,25 ... 55,00 MHz		36,0	42,0	—	dB
Impedance at 41,25 MHz						
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$			—	0,4 || 9,5	—	kΩ || pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$			—	3,3 || 6,3	—	kΩ || pF
Temperature coefficient of frequency		TC_f	—	–72	—	ppm/K

Frequency response





Published by EPCOS AG
Surface Acoustic Wave Components Division, SAW CE MM PD
P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2001. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.