HAMMOND

*Quality Products. Service Excellence.*

# Compact LED Light Kit *LEDLK Series*



Our compact LED light kit provides efficient lighting solution for most enclosure applications without taking up valuable interior space. Available in magnet or screw mounting and AC or DC power options.

## Features

- Housing constructed in transparent plastic.
- Screw mounting and magnet mounting options - see chart.
- Rocker switch or motion sensor options - see chart.
- Easily connect up to ten (10) light kits together in a daisy chain using LEDXXCORDCON cords. (LEDACNS-ECON cannot be daisy chained).
- Connection: 2-pole plug with snap lock; AC: max. 2.5 A / AC 240 V, white connector; DC: max. 2.5 A / DC 60 V, blue connector. (LEDACNS-ECON wired directly, Cage clamp connections).
- Requires hard-wired connection using LEDXXCORDPOW power cord with leads and plu or power brick (not included). (LEDACNS-ECON wired directly, not using accessory power cord).

## Specifications

- Standard LED provide 400 Lm at 120° (1,200 Lm at 360° or equivalent 95W light bulb). HD LED provides 1700 Lm.
- Standard LED lamp length 13.82" (350mm), HD LED Lamp length 23.62" (600mm)
- LED temperature 6,000 to 7,000 K.
- Operating / Storage temperature: -40 to +104 °F (-40 to +40 °C) / -40 to +185 °F (-40 to +85 °C).
- Operating / Storage humidity: max. 90 %RH (non-condensing).
- Service life: 60,000 hrs. at 68 °F (20 °C).
- Max. 5W power consumption (~ 75 W incandescent bulb). HD LED 15W power consumption.
- Protection class / Protection type: II (double insulated) / IP20

Note that the cord on this product is intended to be hard-wired. There are currently no standard plug types for this product.

## Gallery





## Accessories

- Power Cords
- Remote Door Switches

## LED Light Kits

| Part No. | Voltage | On/Off | Mount | Max Daisy Chain |
|---|---|---|---|---|
| **LEDACSWMAG** | 90-260V AC | Switch | Magnet | 10 |
| **LEDACMSMAG** | 90-260V AC | Sensor | Magnet | 10 |
| **LEDACSWSCR** | 90-260V AC | Switch | Screw | 10 |
| **LEDACMSSCR** | 90-260V AC | Sensor | Screw | 10 |
| **LEDACNS-ECON** | 90-260V AC | NA | Screw | NA |
| **LEDDCSWMAG** | 20-60V DC | Switch | Magnet | 10 |
| **LEDDCMSMAG** | 20-60V DC | Sensor | Magnet | 10 |
| **LEDDCSWSCR** | 20-60V DC | Switch | Screw | 10 |
| **LEDDCMSSCR** | 20-60V DC | Sensor | Screw | 10 |

## HD LED Light

| Part No. | Voltage | On/Off | Mount | Max Daisy Chain |
|---|---|---|---|---|
| **HDLED120SCR** | 90-260V AC | Switch | Screw | 8 |

## LED Light Kit Cords

| Part No. | Type | Source | Length |
|---|---|---|---|
| **LEDACCORDPOW** | Power Cord w/leads | AC | 78.75 |
| **LEDDCCORDPOW** | Power Cord w/leads | DC | 78.75 |
| **LEDACCORDCON** | Connector/Daisy Chain Cord | AC | 39.38 |
| **LEDDCCORDCON** | Connector/Daisy Chain Cord | DC | 39.38 |

## Light Channel Hardware

| Part No. | Description |
|---|---|
| **LCMTG1032** | Light channel mounting hardware - 4 x spring nuts/10-32 screws |

Tags: **led**, **light kit**, **rocker switch**, **sensor**, **light strip**

*Data subject to change without notice*

© 2024. Hammond Manufacturing Ltd. All rights reserved.