SIPMOS® Small-Signal-Transistor

Features

- N-channel
- Depletion mode
- d*v*/d*t* rated
- Available with $V_{GS(th)}$ indicator on reel
- Pb-free lead-plating; RoHS compliant

Product Summary

V_{DS}	250	V
$R_{DS(on),max}$	30	Ω
$I_{DSS,min}$	0.03	A

PG-SOT-23



AEC Qualified RoHS Halogen-Free

Type	Package	Tape and Reel Information	Marking	Pb-free
BSS139	PG-SOT-23	H6327: 3000 pcs/ree	STs	Yes
BSS139	PG-SOT-23	H6906: 3000 pcs/reel sorted in $V_{S(th)}$ bands [1)]	STs	Yes

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_A=25 °C	0.10	A
		T_A=70 °C	0.08	
Pulsed drain current	$I_{D,pulse}$	T_A=25 °C	0.4	
Reverse diode d*v*/d*t*	d*v*/d*t*	I_D=0.1 A, V_{DS}=200 V, d*i*/d*t*=200 A/µs, $T_{j,max}$=150 °C	6	kV/µs
Gate source voltage	V_{GS}		±20	V
ESD class (JESD22-A114-HBM)			0 (<250V)	
Power dissipation	P_{tot}	T_A=25 °C	0.36	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
IEC climatic category; DIN IEC 68-1			55/150/56	

[1)] see table on next page and diagram 11

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint	-	-	350	K/W
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=-3 V, I_D=250 µA	250	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=3 V, I_D=56 µA	-2.1	-1.4	-1	
Drain-source cutoff current	$I_{D(off)}$	V_{DS}=250 V, V_{GS}=-3 V, T_j=25 °C	-	-	0.1	µA
		V_{DS}=250 V, V_{GS}=-3 V, T_j=125 °C	-	-	10	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	-	10	nA
On-state drain current	I_{DSS}	V_{GS}=0 V, V_{DS}=10 V	30	-	-	mA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=0 V, I_D=15 mA	-	12.5	30	Ω
		V_{GS}=10 V,I_D=0.1 mA	-	7.8	14	
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=0.08 A	0.060	0.13	-	S
Threshold voltage $V_{GS(th)}$ sorted in bands[2)]						
J	$V_{GS(th)}$	V_{DS}=3 V, I_D=56 µA	-1.2	-	-1	V
K			-1.35	-	-1.15	
L			-1.5	-	-1.3	
M			-1.65	-	-1.45	
N			-1.8	-	-1.6	

[2)] Each reel contains transistors out of one band whose identifying letter is printed on the reel label. A specific band cannot be ordered separately.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=-3 V, V_{DS}=25 V, f=1 MHz	-	60	76	pF
Output capacitance	C_{oss}		-	6.7	8.4	
Reverse transfer capacitance	C_{rss}		-	2.6	3.3	
Turn-on delay time	$t_{d(on)}$	V_{DD}=125 V, V_{GS}=-3...5 V, I_D=0.04 A, R_G=6 Ω	-	5.8	8.7	ns
Rise time	t_r		-	5.4	8.1	
Turn-off delay time	$t_{d(off)}$		-	29	43	
Fall time	t_f		-	182	273	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=200 V, I_D=0.04 A, V_{GS}=-3 to 5 V	-	0.14	0.21	nC
Gate to drain charge	Q_{gd}		-	1.3	2.0	
Gate charge total	Q_g		-	2.3	3.5	
Gate plateau voltage	$V_{plateau}$		-	-0.28	-	V
Reverse Diode						
Diode continous forward current	I_S	T_A=25 °C	-	-	0.10	A
Diode pulse current	$I_{S,pulse}$		-	-	0.4	
Diode forward voltage	V_{SD}	V_{GS}=-3 V, I_F=0.1 A, T_j=25 °C	-	0.81	1.2	V
Reverse recovery time	t_{rr}	V_R=50 V, I_F=0.04 A, di_F/dt=100 A/µs	-	8.6	12.9	ns
Reverse recovery charge	Q_{rr}		-	2.1	3.1	nC

1 Power dissipation

$P_{tot}=f(T_A)$



2 Drain current

$I_D=f(T_A)$; $V_{GS}\geq 10$ V



3 Safe operating area

$I_D=f(V_{DS})$; $T_A=25$ °C; $D=0$

parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p)$

parameter: $D=t_p/T$



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C

parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C

parameter: V_{GS}



7 Typ. transfer characteristics

I_D=f(V_{GS}); $|V_{DS}|>2|I_D|R_{DS(on)max}$



8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C



9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=0.015 A; V_{GS}=0 V



10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{DS}=3 V; I_D=56 µA

parameter: I_D



11 Threshold voltage bands

I_D=f(V_{GS}); V_{DS}=3 V; T_j=25 °C



12 Typ. capacitances

C=f(V_{DS}); V_{GS}=-3 V; f=1 MHz



13 Forward characteristics of reverse diode

I_F=f(V_{SD})

parameter: T_j



15 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=0.1 A pulsed

parameter: V_{DD}



16 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=250 µA



Package Outline:



Footprint:



Packaging:



Dimensions in mm

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2010 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.