OptiMOS™3 Power-Transistor

Features

- MOSFET for ORing and Uninterruptible Power Supply
- Qualified according to JEDEC[1] for target applications
- N-channel
- Logic level
- Ultra-low on-resistance $R_{DS(on)}$
- 100% Avalanche tested
- Pb-free plating; RoHS compliant
- Halogen-free according to IEC61249-2-21

RoHS Halogen-Free

Product Summary

V_{DS}	40	V
$R_{DS(on),max}$	1.1	mΩ
I_D	180	A

PG-TO263-7





Type	Package	Marking
IPB011N04L G	PG-TO263-7	011N04L

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	V_{GS}=10 V, T_C=25 °C	180	A
		V_{GS}=10 V, T_C=100 °C	180	
		V_{GS}=4.5 V, T_C=25 °C	180	
		V_{GS}=4.5 V, T_C=100 °C	180	
Pulsed drain current[2]	$I_{D,pulse}$	T_C=25 °C	1260	
Avalanche current, single pulse[3]	I_{AS}	T_C=25 °C	100	
Avalanche energy, single pulse	E_{AS}	I_D=100 A, R_{GS}=25 Ω	525	mJ
Gate source voltage	V_{GS}		±20	V

[1] J-STD20 and JESD22

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Power dissipation	P_{tot}	T_C=25 °C	250	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - case	R_{thJC}		-	-	0.6	K/W
SMD version, device on PCB	R_{thJA}	minimal footprint	-	-	62	
		6 cm² cooling area[4)]	-	-	40	

Electrical characteristics, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	40	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=200 µA	1.2	-	2	
Zero gate voltage drain current	I_{DSS}	V_{DS}=40 V, V_{GS}=0 V, T_j=25 °C	-	0.1	2	µA
		V_{DS}=40 V, V_{GS}=0 V, T_j=125 °C	-	20	200	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5 V, I_D=100 A	-	1.0	1.4	mΩ
		V_{GS}=10 V, I_D=100 A	-	0.8	1.1	
Gate resistance	R_G		-	1.5	-	Ω
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=100 A	180	370	-	S

[2)] See figure 3 for more detailed information

[3)] See figure 13 for more detailed information

[4)] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=20 V, f=1 MHz	-	22000	29000	pF
Output capacitance	C_{oss}		-	4100	5500	
Reverse transfer capacitance	C_{rss}		-	240	-	
Turn-on delay time	$t_{d(on)}$	V_{DD}=20 V, V_{GS}=10 V, I_D=30 A, R_G=1.6 Ω	-	25	-	ns
Rise time	t_r		-	13	-	
Turn-off delay time	$t_{d(off)}$		-	106	-	
Fall time	t_f		-	21	-	
Gate Charge Characteristics[5)]						
Gate to source charge	Q_{gs}	V_{DD}=20 V, I_D=100 A, V_{GS}=0 to 10 V	-	61	-	nC
Gate charge at threshold	$Q_{g(th)}$		-	33	-	
Gate to drain charge	Q_{gd}		-	27	-	
Switching charge	Q_{sw}		-	55	-	
Gate charge total	Q_g		-	260	346	
Gate plateau voltage	$V_{plateau}$		-	3.0	-	V
Gate charge total	Q_g	V_{DD}=20 V, I_D=100 A, V_{GS}=0 to 4.5 V	-	125	167	nC
Gate charge total, sync. FET	$Q_{g(sync)}$	V_{DS}=0.1 V, V_{GS}=0 to 10 V	-	244	-	
Output charge	Q_{oss}	V_{DD}=20 V, V_{GS}=0 V	-	153	-	
Reverse Diode						
Diode continuous forward current	I_S	T_C=25 °C	-	-	180	A
Diode pulse current	$I_{S,pulse}$		-	-	1260	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=100 A, T_j=25 °C	-	0.82	1.1	V
Reverse recovery charge	Q_{rr}	V_R=20 V, I_F=I_S, di_F/dt=400 A/µs	-	120	-	nC

[5)] See figure 16 for gate charge parameter definition

1 Power dissipation

$P_{tot}=f(T_C)$



2 Drain current

$I_D=f(T_C)$; $V_{GS}\geq 10$ V



3 Safe operating area

$I_D=f(V_{DS})$; $T_C=25$ °C; $D=0$

parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC}=f(t_p)$

parameter: $D=t_p/T$



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C

parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C

parameter: V_{GS}



7 Typ. transfer characteristics

I_D=f(V_{GS}); |V_{DS}|>2|I_D|$R_{DS(on)max}$

parameter: T_j



8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C



9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=100 A; V_{GS}=10 V



10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}; I_D=1mA



11 Typ. capacitances

C=f(V_{DS}); V_{GS}=0 V; f=1 MHz



12 Forward characteristics of reverse diode

I_F=f(V_{SD})

parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω

parameter: $T_{j(start)}$



14 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=100 A pulsed

parameter: V_{DD}



15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=1 mA



16 Gate charge waveforms



Package Outline **PG-TO263-7**

TO263-7-2 / TO263-7-3 / TO263-7-5 / TO263-7-7



FOOTPRINT



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.57	0.169	0.180
A1	0.00	0.25	0.000	0.010
b	0,50	0,70	0.020	0,028
b2	0.50	1.00	0.020	0.039
c	0.33	0.65	0.013	0.026
c2	1,17	1,40	0,046	0,055
D	8.51	9.45	0.335	0.372
D1	6.90	7.90	0.272	0.311
E	9,80	10,31	0,386	0,406
E1	6.50	8.60	0.256	0.339
e	1.27		0.050	
N	6		6	
H	14.61	15.88	0.575	0.625
L	2,29	3,00	0,090	0,118
L1	0.70	1.60	0.028	0.063
L2	1.00	1.78	0.039	0.070
F1	16,05	16,25	0.632	0,640
F2	9.30	9.50	0.366	0.374
F3	4.50	4.70	0.177	0.185
F4	10,70	10,90	0,421	0,429
F5	0.37	0.57	0.015	0.022
F6	0.70	0.90	0.028	0.035

DOCUMENT NO.
Z8B00134765

SCALE 0 5 5 7.5mm

EUROPEAN PROJECTION



ISSUE DATE
05-11-2007

REVISION
01

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.