OptiMOS®-T Power-Transistor


Product Summary


V_{DS}	100	V
$R_{DS(on),max}$	24	mΩ
I_D	35	A

Features

- N-channel - Enhancement mode
- Automotive AEC Q101 qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- RoHS compliant
- 100% Avalanche tested

PG-TO252-3-11





Type	Package	Marking
IPD35N10S3L-26	PG-TO252-3-11	3N10L26

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_C=25°C, V_{GS}=10V	35	A
		T_C=100°C, V_{GS}=10V[1)]	25	
Pulsed drain current[1)]	$I_{D,pulse}$	T_C=25°C	140	
Avalanche energy, single pulse[1)]	E_{AS}	I_D=17A	175	mJ
Avalanche current, single pulse	I_{AS}		35	A
Gate source voltage[2)]	V_{GS}		±20	V
Power dissipation	P_{tot}	T_C=25°C	71	W
Operating and storage temperature	T_j, T_{stg}		-55 ... +175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics[1]						
Thermal resistance, junction - case	R_{thJC}		-	-	2.1	K/W
SMD version, device on PCB	R_{thJA}	minimal footprint	-	-	62	
		6 cm^2 cooling area[3]	-	-	40	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(Br)DSS}$	V_{GS}=0V, I_D= 1mA	100	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=39µA	1.2	1.7	2.4	
Zero gate voltage drain current	I_{DSS}	V_{DS}=80V, V_{GS}=0V, T_j=25°C	-	0.01	0.1	µA
		V_{DS}=80V, V_{GS}=0V, T_j=125°C[1]	-	1	10	
Gate-source leakage current	I_{GSS}	V_{GS}=20V, V_{DS}=0V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5V, I_D=35A	-	24.5	31.9	mΩ
		V_{GS}=10 V, I_D=35 A	-	20.0	24.0	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics[1]						
Input capacitance	C_{iss}	V_{GS}=0V, V_{DS}=25V, f=1MHz	-	2070	2700	pF
Output capacitance	C_{oss}		-	460	600	
Reverse transfer capacitance	C_{rss}		-	50	75	
Turn-on delay time	$t_{d(on)}$	V_{DD}=20V, V_{GS}=10V, I_D=35A, R_G=3.5Ω	-	6	-	ns
Rise time	t_r		-	4	-	
Turn-off delay time	$t_{d(off)}$		-	18	-	
Fall time	t_f		-	3	-	
Gate Charge Characteristics[1]						
Gate to source charge	Q_{gs}	V_{DD}=80V, I_D=35A, V_{GS}=0 to 10V	-	8	10	nC
Gate to drain charge	Q_{gd}		-	5	8	
Gate charge total	Q_g		-	30	39	
Gate plateau voltage	$V_{plateau}$		-	3.7	-	V
Reverse Diode						
Diode continous forward current[1]	I_S	T_C=25°C	-	-	35	A
Diode pulse current[1]	$I_{S,pulse}$		-	-	140	
Diode forward voltage	V_{SD}	V_{GS}=0V, I_F=35A, T_j=25°C	0.6	1	1.2	V
Reverse recovery time[1]	t_{rr}	V_R=50V, I_F=I_S, di_F/dt=100A/µs	-	79	-	ns
Reverse recovery charge[1]	Q_{rr}		-	150	-	nC


[1] Defined by design. Not subject to production test.

[2] -5V to -20V for max. 168 non-consecutive hours.

[3] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.


1 Power dissipation

$P_{tot} = f(T_C)$; $V_{GS} \geq 6$ V



2 Drain current


$I_D = f(T_C)$; $V_{GS} \geq 6$ V



3 Safe operating area

$I_D = f(V_{DS})$; $T_C = 25$ °C; $D = 0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$


parameter: $D = t_p/T$



5 Typ. output characteristics

$I_D = f(V_{DS})$; $T_j = 25$ °C


parameter: V_{GS}



6 Typ. drain-source on-state resistance

$R_{DS(on)} = f(I_D)$; $T_j = 25$ °C


parameter: V_{GS}



7 Typ. transfer characteristics

$I_D = f(V_{GS})$; $V_{DS} = 6$V


parameter: T_j



8 Typ. drain-source on-state resistance

$R_{DS(on)} = f(T_j)$; $I_D = 30$ A; $V_{GS} = 10$ V


α = 0.56



9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j)$; $V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS})$; $V_{GS} = 0$ V; $f = 1$ MHz



11 Typical forward diode characteristicis

IF = f(V_{SD})


parameter: T_j



12 Typ. avalanche characteristics

$I_{AS} = f(t_{AV})$


parameter: $T_{j(start)}$



13 Typical avalanche energy


$E_{AS} = f(T_j)$

parameter: I_D



14 Typ. drain-source breakdown voltage


$V_{(Br)DSS} = f(T_j)$; $I_D = 1$ mA




15 Typ. gate charge

$V_{GS} = f(Q_{gate})$; $I_D = 35$ A pulsed

parameter: V_{DD}



16 Gate charge waveforms



Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2023-06-15

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2023 Infineon Technologies AG

All Rights Reserved.

Do you have any questions about any aspect of this document?

Email: erratum@infineon.com

Document reference
IPD35N10S3L-26-Data-Sheet-13-Infineon

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.
The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (**www.infineon.com**).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact the nearest Infineon Technologies Office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Revision History

Version	Date	Changes
Rev 1.0	21.04.2008	Final data sheet
Rev 1.1	17.05.2011	$I_{D,pulse}$ corrected
Rev 1.2	15.06.2023	$R_{DS(on),max}$ in Product Summary corrected
Rev 1.2	15.06.2023	Diagram 8 Typ. drain-source on-state resistance: used α value clarified
Rev 1.2	15.06.2023	Ratings of Gate Source Voltage V_{GS} refined in footnote [2)]
Rev 1.2	15.06.2023	Corrected diagram 3 safe operating area
Rev 1.2	15.06.2023	Corrected diagram 10 typical capacitances