PD-9001-10GC

Single-Port, 10 Gbps, IEEE 802.3at 30W, Indoor PoE Midspan



Summary

The Microchip PD-9001-10GC is a single-port, high-power solution for remote powering of current and emerging high-power indoor applications. Generating 30W, the PD-9001-10GC enables remote power for a new range of applications including wireless access points, Pan-Tilt-Zoom (PTZ) cameras and videophones.

It complies to IEEE 802.3at PoE standard and is back-ward compatible to IEEE 802.3af. It can power both existing 10/100/1000Base-T network devices and emerging wireless 10 Gbps devices such as wireless access points.

Features

- IEEE 802.3at compliant
- IEEE 802.3af backward compatible
- Guaranteed output power: 30W
- Supports 10/100/1000Base-T and 2.5/5/10 Gbps
- Safe: low power devices receive only the power they need
- Automatic detection and protection of non–standard Ethernet terminals
- Compact design fits easily in WLAN access point and IP cameras installation

Specifications

Feature	Description
Number of Ports	1
Data Rate	10/100/1000 Mbps and 2.5/5/10 Gbps
Input Power Requirement	AC Input Voltage: 100 to 240 Vac AC Input Current: 0.67A AC Frequency: 50 to 60 Hz
Output Power	30W
Power over Ethernet Output	4/5 (+), 7/8 (-) Nominal Output Voltage: 55 VDC
Dimensions	55.8 mm (W) × 33.3 mm (H) × 167 mm (L) 2.2 in. × 1.31 in. × 6.57 in
Net Weight	400g
Connectors	Shielded RJ-45, CAT6A
Indicators	AC Power (Yellow) Channel Power (Green)
Environmental Conditions	Operating Ambient Temperature: 32°F to 104°F (0°C to +40°C) @ 30W 32°F to 131°F (0°C to +55°C) @ 15W Operating Humidity: Maximum 90%, Non-condensing Storage Temperature: –4°F to +158°F (–20°C to +70°C) Storage Humidity: Maximum 95%, Non-condensing
Hazardous Substances	CE, WEEE
Warranty	1-year
Regulatory Compliance	IEEE 802.3at (PoE)
Electromagnetic Emission and Immunity	FCC Part 15, Class B EN 55032 Class B EN 55035 VCCI
Safety	UL/EN/IEC 62368-1 Please contact Microchip for a complete list of certifications

Technical Support

For technical support please visit the Microchip Technical Support Portal www.microchip.com/support.

Ordering Information

Product Name	Part Number	Description
PD-9001-10GC/AC-xx	PD-9001-10GC	Single Port, 10 Gbps, IEEE 802.3at 30W, Indoor PoE Midspan
PD-9001-10GC/AC-US: US Power Cord		
PD-9001-10GC/AC-EU: EU Power Cord		
PD-9001-10GC/AC-UK: UK Power Cord		
PD-9001-10GC/AC-AU: AU Power Cord		

Contact Microchip for other options

About Microchip mPoE

Microchip multi-Power over Ethernet (mPoE) is a technology that powers any wired network device seamlessly and efficiently, making it the ideal solution for Ethernet-based applications. Leveraging a uniquely designed algorithm, this technology solves interoperability issues between different PoE standards and legacy solutions to provide an international network power standard. As a pioneer in PoE technology, we offer a comprehensive end-to-end portfolio of PoE solutions comprised of PoE ICs and PoE systems (midspans/injectors and switches).

The Microchip name and logo and the Microchip logo are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks mentioned herein are property of their respective companies.
© 2023, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved. 3/23
DS00003357C