NIF5003N

Preferred Device

Self-Protected FET with Temperature and Current Limit

42 V, 14 A, Single N−Channel, SOT−223

HDPlus™ devices are an advanced series of power MOSFETs which utilize ON Semiconductors latest MOSFET technology process to achieve the lowest possible on−resistance per silicon area while incorporating smart features. Integrated thermal and current limits work together to provide short circuit protection. The devices feature an integrated Drain−to−Gate Clamp that enables them to withstand high energy in the avalanche mode. The Clamp also provides additional safety margin against unexpected voltage transients. Electrostatic Discharge (ESD) protection is provided by an integrated Gate−to−Source Clamp.

Features

- Short Circuit Protection/Current Limit
- Thermal Shutdown with Automatic Restart
- I_{DSS} Specified at Elevated Temperature
- Avalanche Energy Specified
- Slew Rate Control for Low Noise Switching
- Overvoltage Clamped Protection
- Pb−Free Packages are Available

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage Internally Clamped	V_{DSS}	42	Vdc
Gate−to−Source Voltage	V_{GS}	±14	Vdc
Drain Current Continuous	I_D	Internally Limited	
Total Power Dissipation @ T_A = 25°C (Note 1) @ T_A = 25°C (Note 2)	P_D	 1.25 1.9	W
Thermal Resistance Junction−to−Case Junction−to−Ambient (Note 1) Junction−to−Ambient (Note 2)	 $R_{\theta JC}$ $R_{\theta JA}$ $R_{\theta JA}$	 12 100 65	°C/W
Single Pulse Drain−to−Source Avalanche Energy (V_{DD} = 25 Vdc, V_{GS} = 5.0 Vdc, I_L = 7.0 Apk, L = 9.5 mH, R_G = 25 Ω)	E_{AS}	233	mJ
Operating and Storage Temperature Range (Note 3)	T_J, T_{stg}	−55 to 150	°C


Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. Surface mounted onto minimum pad size (0.412″ square) FR4 PCB, 1 oz cu.
2. Mounted onto 1″ square pad size (1.127″ square) FR4 PCB, 1 oz cu.
3. Normal pre−fault operating range. See thermal limit range conditions.

ON Semiconductor®

http://onsemi.com


V_{DSS} (Clamped)	$R_{DS(on)}$ TYP	I_D MAX (Limited)
42 V	53 mΩ @ 10 V	14 A





SOT−223
CASE 318E
STYLE 3

MARKING DIAGRAM



A = Assembly Location
Y = Year
W = Work Week
5003N = Specific Device Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2008

MOSFET ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Drain−to−Source Clamped Breakdown Voltage (V_{GS} = 0 Vdc, I_D = 250 μAdc) (V_{GS} = 0 Vdc, I_D = 250 μAdc, T_J = −40°C to 150°C)	$V_{(BR)DSS}$	 42 40	 46 45	 51 51	 Vdc mV/°C
Zero Gate Voltage Drain Current (V_{DS} = 32 Vdc, V_{GS} = 0 Vdc) (V_{DS} = 32 Vdc, V_{GS} = 0 Vdc, T_J = 150°C)	I_{DSS}	 − −	 0.6 2.5	 5.0 −	μAdc
Gate Input Current (V_{GS} = 5.0 Vdc, V_{DS} = 0 Vdc)	I_{GSS}	−	50	125	μAdc
ON CHARACTERISTICS					
Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = 1.2 mAdc) Threshold Temperature Coefficient (Negative)	$V_{GS(th)}$	 1.0 −	 1.7 5.0	 2.2 −	 Vdc mV/°C
Static Drain−to−Source On−Resistance (Note 4) (V_{GS} = 10 Vdc, I_D = 3.0 Adc, T_J @ 25°C) (V_{GS} = 10 Vdc, I_D = 3.0 Adc, T_J @ 150°C)	$R_{DS(on)}$	 − −	 53 95	 68 123	mΩ
Static Drain−to−Source On−Resistance (Note 4) (V_{GS} = 5.0 Vdc, I_D = 3.0 Adc, T_J @ 25°C) (V_{GS} = 5.0 Vdc, I_D = 3.0 Adc, T_J @ 150°C)	$R_{DS(on)}$	 − −	 63 105	 76 135	mΩ
Source−Drain Forward On Voltage (I_S = 7.0 A, V_{GS} = 0 V)	V_{SD}	−	0.95	1.1	V
SWITCHING CHARACTERISTICS					
Turn−on Time (V_{in} to 90% I_D)	R_L = 4.7 Ω, V_{in} = 0 to 10 V, V_{DD} = 12 V	$T_{(on)}$	−	16	20	μs
Turn−off Time (V_{in} to 10% I_D)	R_L = 4.7 Ω, V_{in} = 10 to 0 V, V_{DD} = 12 V	$T_{(off)}$	−	80	100	μs
Slew Rate On	R_L = 4.7 Ω, V_{in} = 0 to 10 V, V_{DD} = 12 V	$-dV_{DS}/dt_{on}$	−	1.4	−	V/μs
Slew Rate Off	R_L = 4.7 Ω, V_{in} = 10 to 0 V, V_{DD} = 12 V	dV_{DS}/dt_{off}	−	0.5	−	V/μs

SELF PROTECTION CHARACTERISTICS (T_J = 25°C unless otherwise noted) (Note 5)

Current Limit	(V_{GS} = 5.0 Vdc) V_{DS} = 10 V (V_{GS} = 5.0 Vdc, T_J = 150°C)	I_{LIM}	12 7.0	18 13	24 18	Adc
Current Limit	(V_{GS} = 10 Vdc) V_{DS} = 10 V (V_{GS} = 10 Vdc, T_J = 150°C)	I_{LIM}	18 13	22 18	30 25	Adc
Temperature Limit (Turn−off)	V_{GS} = 5.0 Vdc	$T_{LIM(off)}$	150	175	200	°C
Thermal Hysteresis	V_{GS} = 5.0 Vdc	$\Delta T_{LIM(on)}$	−	15	−	°C
Temperature Limit (Turn−off)	V_{GS} = 10 Vdc	$T_{LIM(off)}$	150	165	185	°C
Thermal Hysteresis	V_{GS} = 10 Vdc	$\Delta T_{LIM(on)}$	−	15	−	°C

ESD ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Electro−Static Discharge Capability	Human Body Model (HBM)	ESD	4000	−	−	V
Electro−Static Discharge Capability	Machine Model (MM)	ESD	400	−	−	V

4. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2%.
5. Fault conditions are viewed as beyond the normal operating range of the part.

TYPICAL PERFORMANCE CURVES




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate−to−Source Voltage




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL PERFORMANCE CURVES




Figure 7. Diode Forward Voltage vs. Current

ORDERING INFORMATION

Device	Package	Shipping†
NIF5003NT1	SOT−223	1000 / Tape & Reel
NIF5003NT1G	SOT−223 (Pb−Free)	1000 / Tape & Reel
NIF5003NT3	SOT−223	4000 / Tape & Reel
NIF5003NT3G	SOT−223 (Pb−Free)	4000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


HDPlus is a trademark of Semiconductor Components Industries, LLC (SCILLC)





SCALE 1:1


SOT−223 (TO−261)
CASE 318E−04
ISSUE R

DATE 02 OCT 2018










NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D & E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.200MM PER SIDE.
4. DATUMS A AND B ARE DETERMINED AT DATUM H.
5. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
6. POSITIONAL TOLERANCE APPLIES TO DIMENSIONS b AND b1.

	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	1.50	1.63	1.75
A1	0.02	0.06	0.10
b	0.60	0.75	0.89
b1	2.90	3.06	3.20
c	0.24	0.29	0.35
D	6.30	6.50	6.70
E	3.30	3.50	3.70
e	2.30 BSC		
L	0.20	---	---
L1	1.50	1.75	2.00
He	6.70	7.00	7.30
θ	0°	---	10°



RECOMMENDED MOUNTING FOOTPRINT

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

SOT−223 (TO−261)
CASE 318E−04
ISSUE R

DATE 02 OCT 2018

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. CATHODE
3. NC
4. CATHODE

STYLE 3:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 4:
PIN 1. SOURCE
2. DRAIN
3. GATE
4. DRAIN

STYLE 5:
PIN 1. DRAIN
2. GATE
3. SOURCE
4. GATE

STYLE 6:
PIN 1. RETURN
2. INPUT
3. OUTPUT
4. INPUT

STYLE 7:
PIN 1. ANODE 1
2. CATHODE
3. ANODE 2
4. CATHODE

STYLE 8:
CANCELLED

STYLE 9:
PIN 1. INPUT
2. GROUND
3. LOGIC
4. GROUND


STYLE 10:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 11:
PIN 1. MT 1
2. MT 2
3. GATE
4. MT 2

STYLE 12:
PIN 1. INPUT
2. OUTPUT
3. NC
4. OUTPUT

STYLE 13:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

GENERIC MARKING DIAGRAM*



A = Assembly Location
Y = Year
W = Work Week
XXXXX = Specific Device Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98ASB42680B	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	SOT−223 (TO−261)	PAGE 2 OF 2

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales