

PFM0093

Nonskid floor tape used to create a high-traction surface to prevent slips, trips, and falls, 2in x 60ft, PVC/Aluminum Oxide, Tape has aggressive 60-grit aluminum oxide compound layer impregnated onto a thick PVC base, Peel off back liner to install quickly with high-tack acrylic adhesive back, Meets ANSI/National Flooring Safety Institute (NFSI) B101.1 and OSHA 29 CFR 1910.24(f), Yellow

Sold in US and Canada only

Specs | Packaging Details | Documents

Add to Favorites | Add to BOM

Color	Yellow
Material	PVC/Aluminum Oxide
Overall Width (mm)	50.8
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Note	Sold in US and Canada only
Minimum Operating Temperature (°C)	-28
Minimum Operating Temperature (°F)	-20
Application	Create a high-traction surface to prevent slips, trips, and falls.
Dimensions (In.)	2" x 60-ft
Environment	3 years
Legend	NONE
Operating Temperature	-20°F - 140°F
Part Features	Place anti-skid floor tape on walkways, ramps, loading docks, steps, and stairways to help maintain a safe-stepping workplace on wet or greasy floors, Tape has aggressive 60-grit aluminum oxide compound layer impregnated onto a thick PVC base, Peel off back liner to install quickly with high-tack acrylic adhesive back, Meets ANSI/National Flooring Safety Institute (NFSI) B101.1 and OSHA 29 CFR 1910.24(f).
UL Listed	No
RoHS Compliancy Status	Compliant
Min. Order Qty.	1