

PVT-1066

Safety Tags, 5.75in x 3.25in, Front: "DANGER BARRICADE TAG REASON INSTALLED ____ DATE ___ BY ___ TIME ___ DESCRIPTION OF HAZARD ___", Back: "DANGER BARRICADE TAG DO NOT REMOVE NOTIFY CONTACT PERSON FOR ENTRY INSTRUCTIONS CONTACT NAME ____ DEPT ____ PHONE ____", Polyethylene Plastic is high-strength and resists chemicals, tears, and abrasions, Protects information from moisture, chemicals, dirt, and tampering, Mar-resistant, matte surface is easy to write on with pen or marker, Red/Black on White, Pack of 5.

Sold in US and Canada only

Specs | Packaging Details | Documents

Add to Favorites | Add to BOM

Color	Red/Black/White
Material	Polyethylene Plastic
Overall Width (In.)	3.25
Overall Width (mm)	82.6
Overall Height (In.)	5.75
Overall Height (mm)	146
Note	Sold in US and Canada only
Application	Safety tags meet OSHA 29 CFR 1910.145 and ANSI Z535 requirements to identify temporary hazards until they're eliminated, or hazardous operations are complete.
Dimensions (In.)	5.75 x 3.25
Environment	2-3 years
Legend	FRONT: DANGER BARRICADE TAG REASON INSTALLED__ BY__ DATE__ TIME__ DESCRIPTION OF HAZARD_____ / BACK: DANGER BARRICADE TAG DO NOT REMOVE NOTIFY CONTACT PERSON FOR ENTRY INSTRUCTIONS CONTACT NAME:__ DEPT:__ PHONE:__
Maximum Operating Temperature (°C)	75
Maximum Operating Temperature (°F)	168
Minimum Operating Temperature (°C)	-67
Minimum Operating Temperature (°F)	-90
Operating Temperature	-90°F - 168°F
Part Features	High-strength 15-mil plastic tag for use in tough industrial environments, Resists chemicals, tears, and abrasions, Mar-resistant, matte surface is easy to write on with pen or marker, Top has 0.375 hole, reinforced with brass grommet, Pack of 5.
Thickness (In.)	0.50
UL Listed	No
RoHS Compliancy Status	Compliant
Min. Order Qty.	1