

PVT-1067

Safety Tags, 5.75in x 3.25in, Front: "CAUTION BARRICADE TAG REASON INSTALLED ____ BY ____ DATE ____ TIME ____ DESCRIPTION OF HAZARD _____ ", Back: "CAUTION BARRICADE TAG DO NOT REMOVE NOTIFY CONTACT PERSON FOR ENTRY INSTRUCTIONS CONACT NAME ____ DEPT ____ PHONE ____", Polyethylene Plastic is high-strength and resists chemicals, tears, and abrasions, Protects information from moisture, chemicals, dirt, and tampering, Mar-resistant, matte surface is easy to write on with pen or marker, Black on Yellow, Pack of 5.

Sold in US and Canada only

Specs | Packaging Details | Documents

Add to Favorites | Add to BOM

Note	Sold in US and Canada only
Application	Safety tags meet OSHA 29 CFR 1910.145 and ANSI Z535 requirements to identify temporary hazards until they're eliminated, or hazardous operations are complete.
CE Compliant	No
Color	Black/Yellow
Dimensions (In.)	5.75 x 3.25
Environment	2-3 years
Height (In.)	5.75
Height (mm)	146.0
Legend	FRONT: CAUTION BARRICADE TAG REASON INSTALLED_____ BY__ DATE__ TIME__ DESCRIPTION OF HAZARD_____ / BACK: CAUTION BARRICADE TAG DO NOT REMOVE NOTIFY CONTACT PERSON FOR ENTRY INSTRUCTIONS CONTACT NAME:__ DEPT:__ PHONE:__
Material	Polyethylene Plastic
Operating Temperature	-90°F - 168°F
Part Features	High-strength 15-mil plastic tag for use in tough industrial environments, Resists chemicals, tears, and abrasions, Mar-resistant, matte surface is easy to write on with pen or marker, Top has 0.375 hole, reinforced with brass grommet, Pack of 5.
Thickness (In.)	0.50
UL Listed	No
Width (In.)	3.25
Width (mm)	82.6
RoHS Compliancy Status	Compliant
Min. Order Qty.	1

On a scale of zero to 10, how likely are you to recommend Panduit to a friend, partner or colleague?

0 1 2 3 4 5 6 7 8 9 10

Not likely Most likely