

PVT-1128

Safety Tags, 5.75" x 3.25", 'TO USE FIRE EXTINGUISHER -PULL PIN -AIM AT BASE OF FIRE -SQUEEZE HANDLE -SWEEP SIDE TO SIDE, / BACK: FIRE EXTINGUISHER INSPECTION RECORD' (legend), Polyethylene Plastic, Red/Black on White, 5 pc.
Sold in US and Canada only

Specs | Packaging Details | Documents

Add to Favorites | Add to BOM

Note	Sold in US and Canada only
Application	Safety tags meet OSHA 29 CFR 1910.145 and ANSI Z535 requirements to identify temporary hazards until they're eliminated, or hazardous operations are complete.
CE Compliant	No
Color	Red/Black/White
Dimensions (In.)	5.75" x 3.25"
Environment	2-3 years
Height (In.)	5.75
Height (mm)	146.05
Legend	TO USE FIRE EXTINGUISHER -PULL PIN -AIM AT BASE OF FIRE -SQUEEZE HANDLE -SWEEP SIDE TO SIDE, / BACK: FIRE EXTINGUISHER INSPECTION RECORD
Material	Polyethylene Plastic
Operating Temperature	-90°F to 168°F
Part Features	High-strength 15-mil plastic tag for use in tough industrial environments, Resists chemicals, tears, and abrasions, Mar-resistant, matte surface is easy to write on with pen or marker, Top has 0.375" hole, reinforced with brass grommet, Pack of 5.
Thickness (In.)	0.5
UL Listed	No
Width (In.)	3.25
Width (mm)	82.55
RoHS Compliancy Status	Compliant
Min. Order Qty.	1.0000