RAFIX 22 QR - LED unit, yellow LED, 230 V, without coupling

5.00.070.086/0400



Dimensions	
Dimensions without coupling	46 x 10 x 39.5 mm
Mounting depth without cable	56.4 mm

Mechanical design	
Mounting	snap on coupling and actuator
LED color	yellow
Terminals	screw terminals
Terminal marking	X1 = anode, X2 = cathode

Lamp characteristics	
Operating voltage	AC 230 V
Max. current, I_F	16 mA

Other specifications	
Robustness	acc. to IEC 60947-5-1
Shock resistance acc. to IEC 60068-2-27	50 g at 11 ms, amplitude half sinusoidal
Resistance to vibrations acc. to IEC 60068-2-6	10 g at 40 ... 500 Hz
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Ambient temp. operating max.	+65 °C
Storage temperature min.	-40 °C
Ambient temp. operating min.	-20 °C
Storage temperature max.	+80 °C
Hot wire ignition acc. to IEC 60695-2-1	yes
ROHS compliant	yes
REACH compliant	yes

Technical data are approximate and intended solely for general orientation in the selection of a product.
Subject to modifications and errors. Images and other graphics may only be similar.
For more information, refer to www.rafi.de chapter Imprint / Data Protection.