Product data sheet
Characteristics

ATV61HU55N4T1
SPEEDDRIVE7.5HP460VATV61+CONDUIT BOX



Main

Asynchronous motor control profile	Variable torque standard
Device short name	ATV61
Range of Product	Altivar 61

Complementary

Line Rated Current	14.3 A
Cable entry	Type 1 conduit entry outdoor
Communication Port Protocol	CANopen Modbus
Input voltage	400/480 V AC
Keypad Type	LCD keypad
Maximum Horse Power Rating	7.5 hp
Motor power kW	5.5 kW
Phase	3 phase input 3 phase output
Output voltage	<= rated supply voltage

Environment

EMC filter	Class A EMC filter integrated
IP Degree of Protection	IP20
NEMA degree of protection	No enclosure rating (open device)
Protective treatment	None

Ordering and shipping details

Category	22137-ATV61 7.5 THRU 50 HP DRIVES
Discount Schedule	CP4C
GTIN	00785901522591
Package weight(Lbs)	14.77 lb(US) (6.700 kg)
Returnability	No
Country of origin	CN

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.