Product data sheet

Specifications



servo motor BMH, Lexium 32, 62.5Nm, 3800rpm, untapped shaft, with brake, IP65, IP67, 16bit encoder

BMH2052P26F2A

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device short name	BMH
Product or Component Type	Servo motor
Maximum mechanical speed	3800 rpm
Continuous stall torque	553.2 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 400 V, three phase 553.2 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 480 V, three phase
Peak stall torque	1504.6 lbf.in (170 N.m) LXM32.D72N4 24 A, 400 V, three phase 1504.6 lbf.in (170 N.m) LXM32.D72N4 24 A, 480 V, three phase
Nominal output power	6500 W LXM32.D72N4 24 A, 400 V, three phase 6500 W LXM32.D72N4 24 A, 480 V, three phase
Nominal torque	368.2 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 400 V, three phase 368.2 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 480 V, three phase
Nominal speed	1500 rpm LXM32.D72N4 24 A, 400 V, three phase 1500 rpm LXM32.D72N4 24 A, 480 V, three phase
Product compatibility	LXM32.D72N4 400...480 V three phase
Shaft end	Smooth shaft
IP Degree of Protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	32768 points/turn
Holding brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 32
[Us] rated supply voltage	480 V
Phase	Three phase
Continuous stall current	24.2 A
Continuous power	7.85 W
Maximum current Irms	72 A LXM32.D72N4
Maximum permanent current	96.8 A
Second shaft	Without second shaft end
Shaft diameter	1.5 in (38 mm)
Shaft length	3.1 in (80 mm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Feedback type	Single turn SinCos Hiperface
Holding torque	708.06 lbf.in (80 N.m) holding brake
Motor flange size	8.07 in (205 mm)
Number of motor stacks	2
Torque constant	2.6 N.m/A 248 °F (120 °C)
Back emf constant	161 V/krpm 248 °F (120 °C)
Number of motor poles	10
Rotor inertia	145 kg.cm²
Stator resistance	0.3 Ohm 68 °F (20 °C)
Stator inductance	5.6 mH 68 °F (20 °C)
Stator electrical time constant	18.7 ms 68 °F (20 °C)
Maximum radial force Fr	4200 N 1000 rpm 3330 N 2000 rpm 2910 N 3000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
type of cooling	Natural convection
Length	17.9 in (454.5 mm)
Centring collar diameter	7.09 in (180 mm)
centring collar depth	0.2 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.6 in (14 mm)
Circle diameter of the mounting holes	8.5 in (215 mm)
Net Weight	107.8 lb(US) (48.9 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3606485203348
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.17 in (36.0 cm)
Package 1 Width	12.20 in (31.0 cm)
Package 1 Length	28.74 in (73.0 cm)
Package 1 Weight	127.9 lb(US) (58.0 kg)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	**7259**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**A7df881f-135f-4256-b8c2-ea55d4c9a151**
China RoHS Regulation	**China RoHS declaration**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
WEEE	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**
Take-back	**No**