Product data sheet

Specifications



servo motor BSH, Lexium 32, 0.38N.m, 9000rpm, 40mm, keyed shaft, 16 Sincos single turn, with brake, IP65

BSH0402P36F2A

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device short name	BSH
Product or Component Type	Servo motor
Maximum mechanical speed	10000 rpm
Continuous stall torque	3.36 lbf.in (0.38 N.m) LXM32.U60N4 1.5 A, 480 V, three phase 3.36 lbf.in (0.38 N.m) LXM32.U60N4 1.5 A, 400 V, three phase 3.36 lbf.in (0.38 N.m) LXM32.U45M2 1.5 A, 230 V, single phase
Peak stall torque	12.13 lbf.in (1.37 N.m) LXM32.U60N4 1.5 A, 480 V, three phase 12.13 lbf.in (1.37 N.m) LXM32.U60N4 1.5 A, 400 V, three phase 12.13 lbf.in (1.37 N.m) LXM32.U45M2 1.5 A, 230 V, single phase
Nominal output power	275 W LXM32.U60N4 1.5 A, 480 V, three phase 289 W LXM32.U60N4 1.5 A, 400 V, three phase 152 W LXM32.U45M2 1.5 A, 230 V, single phase
Nominal torque	2.584 lbf.in (0.292 N.m) LXM32.U60N4 1.5 A, 480 V, three phase 2.717 lbf.in (0.307 N.m) LXM32.U60N4 1.5 A, 400 V, three phase 3.222 lbf.in (0.364 N.m) LXM32.U45M2 1.5 A, 230 V, single phase
Nominal speed	9000 rpm LXM32.U60N4 1.5 A, 480 V, three phase 9000 rpm LXM32.U60N4 1.5 A, 400 V, three phase 4000 rpm LXM32.U45M2 1.5 A, 230 V, single phase
Shaft end	Keyed
IP Degree of Protection	IP65 standard
Speed feedback resolution	32768 points/turn
Holding brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 32
supply voltage max	400 V
Phase	Three phase
Continuous stall current	1.5 A
maximum continuous power	398 W
Maximum current Irms	6 A LXM32.U60N4 480 V 6 A LXM32.U60N4 400 V 6 A LXM32.U45M2 230 V
Maximum permanent current	1.5 A
Switching frequency	8 kHz

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Second shaft	Without second shaft end
Shaft diameter	0.3 in (8 mm)
Shaft length	1.0 in (25 mm)
key width	0.5 in (12 mm)
Feedback type	Single turn SinCos Hiperface
Holding torque	3.5 lbf.in (0.4 N.m) holding brake
Motor flange size	1.6 in (40 mm)
Number of motor stacks	2
Torque constant	0.253 N.m/A 248 °F (120 °C)
Back emf constant	18 V/krpm 68 °F (20 °C)
Number of motor poles	10
Rotor inertia	0.0588 kg.cm²
Stator resistance	11.6 Ohm 68 °F (20 °C)
Stator inductance	12.8 mH 68 °F (20 °C)
Stator electrical time constant	1.1 ms 68 °F (20 °C)
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	5.8 W
type of cooling	Natural convection
Length	4.7 in (119.4 mm)
Centring collar diameter	1.2 in (30 mm)
centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.2 in (4.5 mm)
Circle diameter of the mounting holes	1.8 in (46 mm)
Net Weight	1.8 lb(US) (0.8 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3606485467337
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.33 in (11.0 cm)
Package 1 Width	6.69 in (17.0 cm)
Package 1 Length	9.45 in (24.0 cm)
Package 1 Weight	22.1 oz (627.0 g)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
China RoHS Regulation	**China RoHS declaration**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

WEEE	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**
Take-back	**No**