Micro Battery
MS Lithium Rechargeable Battery
MS421R (Reflowable)
MS621R (Reflowable)
MS414GE
MS412FE
MS518SE
MS614SE
MS621FE
MS920SE
MS621T (Wide temperature range)
MS920T (Wide temperature range)
TS Lithium Rechargeable Battery
TS621E
TS920E
ML Lithium Rechargeable Battery
ML414H
Chip type Electric Double Layer Capacitor
CPH3225A
CPX3225A752D
CPM3225A
Silver Oxide Battery
SEIZAIKEN
Cross reference chart
SEIZAIKEN's new usage except watches
Silver Oxide Battery Expiration Guide
For Your Safety
Micro battery's new challenge for medical devices
Support
Global Network
Contact Us
Sitemap

Micro Battery Products Catalog PDF DOWNLOAD

TS Lithium Rechargeable Battery TS920E


SPECIFICATIONS

Type	TS920E
Nominal Voltage(V)	1.5
Charge Voltage(V)	1.6 to 3.0
Nominal Capacity (Voltage Range V) (mAh)	5.5 (2.3 to 1.0)
Internal Impedance(Ω)	20
Standard Discharge Current(mA)	0.05
Cycle Life (Time)100% D.O.D(Depth of Discharge)	50
Cycle Life (Time)20% D.O.D(Depth of Discharge)	1000
Size Diameter(mm)	9.5
Size Height(mm)	2.0
Weight(g)	0.46



TS920E FL27E

Terminals




Click to enlarge


CHARACTERISTICS

Click to enlarge.


Charge/Discharge Characteristics




Charge Voltage Characteristics




Temperature Characteristics



High Temperature Storage Characteristics (60℃)



Float-Charge Characteristics (60℃)



Please contact us for more details.

Inquiry Form

Copyright © Seiko Instruments Inc. 2020, All Rights Reserved.