SIEMENS

Data sheet 3RW5900-0CC00

COM connecting cable 0.3 m for 3RW50



Figure similar

product brand name	SIRIUS
product category	Connecting cables
product designation	COM connecting cable
design of the product	0.3 m, round
manufacturer's article number	
● of soft starter	3RW50
Substance Prohibitance (Date)	09/23/2019
Ambient conditions	
ambient temperature during storage and transport	-40 ... +80 °C
Safety related data	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Certificates/ approvals

General Product Approval				For use in hazardous locations	Declaration of Conformity
CSA	Confirmation	UL	EAC	Explosion Protection Certificate	UKCA

Declaration of Conformity	Test Certificates	Marine / Shipping			
EG-Konf.	Type Test Certificates/Test Report	ABS	LRS	PRS	DNV·GL

other

Confirmation

Further information

Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business
Siemens is working on the renewal of the current EAC certificates.

Subject to change without notice
© Copyright Siemens

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5900-0CC00

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5900-0CC00

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RW5900-0CC00

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5900-0CC00&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current
https://support.industry.siemens.com/cs/ww/en/ps/3RW5900-0CC00/char

Characteristic: Installation altitude
http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5900-0CC00&objecttype=14&gridview=view1

Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917

---

last modified: 12/15/2020

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens