SIEMENS

Data sheet 3RW5950-0GL20



Spring flap for 3RW55/52 without cutout

product designation	Hinged cover
design of the product	Without cutout
manufacturer's article number	
● of soft starter	3RW51
● of soft starter	3RW52
● of soft starter	3RW55
Substance Prohibitance (Date)	02/15/2018
Ambient conditions	
ambient temperature during storage	-40 ... +80 °C

Certificates/ approvals

General Product Approval		For use in hazardous locations	Declaration of Conformity		Test Certificates
Confirmation	EAC	Explosion Protection Certificate	UKCA	CE EG-Konf.	Type Test Certificates/Test Report

Marine / Shipping				other
ABS	LRS	PRS	DNV·GL	Confirmation

Further information

Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business
Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).
Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5950-0GL20
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5950-0GL20
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL20
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5950-0GL20&lang=en
Characteristic: Tripping characteristics, I²t, Let-through current
https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL20/char

Subject to change without notice
© Copyright Siemens

Characteristic: Installation altitude
http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5950-0GL20&objecttype=14&gridview=view1
Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917

---

last modified: 1/18/2021

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens