SIEMENS

Data sheet 6GK5204-0BA00-2KB2



SCALANCE X204RNA; redundant network access; 4x 100 Mbit/s RJ45 ports; LED diagnostics; error-signaling contact with set push-button; redundant power supply; network management; including electronic manual on CD-ROM, C-PLUG optional for PRP networks;

product type designation	**SCALANCE X204RNA**
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	4
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	4
interfaces / other	
number of electrical connections	
● for signaling contact	1
● for power supply	1
type of electrical connection	
● for signaling contact	2-pole terminal block
● for power supply	4-pole terminal block
design of the removable storage	
● C-PLUG	Yes
signal inputs/outputs	
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	3.5 W
● supply voltage / 1 / rated value	19.2 ... 28.8 V
● consumed current / 1 / maximum	0.15 A
● type of electrical connection / 1 / for power supply	4-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	2.0 A
ambient conditions	
ambient temperature	
● during operation	-40 ... +60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %

Subject to change without notice
© Copyright Siemens

protection class IP	IP20
design, dimensions and weights	
design	compact
width	45 mm
height	100 mm
depth	87 mm
net weight	0.23 kg
fastening method	
● 35 mm top hat DIN rail mounting	Yes
● wall mounting	Yes
● S7-300 rail mounting	No
● S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	No
● port mirroring	No
● multiport mirroring	No
● with IRT / PROFINET IO switch	No
● PROFINET IO diagnosis	No
product function / switch-managed	No
protocol / is supported	
● Telnet	No
● HTTP	Yes
● HTTPS	Yes
● TFTP	No
● FTP	No
● BOOTP	No
● GMRP	No
● DCP	Yes
● LLDP	No
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
● IGMP (snooping/querier)	No
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
product functions / redundancy	
product function	
● ring redundancy	No
● High Speed Redundancy Protocol (HRP)	No
● high speed redundancy protocol (HRP) with redundancy manager	No
● high speed redundancy protocol (HRP) with standby redundancy	No
protocol / is supported / Media Redundancy Protocol (MRP)	No
product function	
● media redundancy protocol (MRP) with redundancy manager	No
● High-availability Seamless Redundancy (HSR)	No
● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	Yes

Subject to change without notice
© Copyright Siemens

● High-availability Seamless Redundancy (HSR) and Parallel Redundancy Protocol (PRP) coupling	No
● passive listening	No
product functions / security	
protocol / is supported	
● SSH	Yes
product functions / time	
product function	
● SICLOCK support	No
protocol / is supported	
● NTP	No
● SNTP	Yes
standards, specifications, approvals	
standard	
● for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4, FM16US0205X
● for emitted interference	EN 61000-6-4:2001 (Class A)
● for interference immunity	EN 61000-6-4:2001
MTBF	92.45 a
reference code	
● according to IEC 81346-2	KF
● according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X
certificate of suitability	
● CCC / for hazardous zone according to GB standard	Yes
● CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-4:2001
● C-Tick	Yes
● KC approval	Yes
● railway application in accordance with EN 50155	No
● railway application in accordance with EN 50124-1	No
● IEC 61850-3	No
standards, specifications, approvals / marine classification	
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Germanische Lloyd (GL)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
● Royal Institution of Naval Architects (RINA)	No
accessories	
product extension / optional / C-PLUG	Yes
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or

© Copyright Siemens

	networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	5/27/2023

Subject to change without notice
© Copyright Siemens