We are still shipping! When you place an order, we will ship as quickly as possible. We are actively monitoring the COVID-19 situation; please see all updates here. Thank you for your continued support.



images are CC BY 2.0

SHARE

5.0" TFT Display with Resistive Touch

LCD-16018 ROHS

DESCRIPTION FEATURES DOCUMENTS

- Resistive touch panel
- Viewing Direction: 12:00
- Gray Scale Inversion Direction: 6:00
- Active Area (W x H): 108.00 × 64.80 mm
- Dot Pitch: (W x H) 0.135 x 0.135 mm
- Driver IC: Source: ILI6122 Gate: ILI5960
- BackLight Type: 12 LEDs
- Display Resolution Pixels: 800 x 480
- Interface Type: Parallel RGB 24-bit
- Surface Luminance: 400 cd/m2 (typical)
- Color Depth: 16.7 M
- Pixel Arrangement: RGB Vertical Stripe
- Surface Treatment: AG
- Input Voltage: 3.3 V (typical)
- Module Size: 120.70 x 75.80 x 4.10 mm
- Operating Temperature Range: -20 C to + 70 C

Tags

LCD RESISTIVE TFT

COMMENTS 0 REVIEWS 0

Comments

Looking for answers to technical questions?

We welcome your comments and suggestions below. However, if you are looking for solutions to technical questions please see our Technical Assistance page.

Log in or register to post comments.

STAY IN TOUCH WITH US

Email address SUBMIT

Weekly product releases, special offers, and more.





