SuperChassis 504-203B



Key Features

1. Mini 1U Chassis
2. 200W High-efficiency Power Supply **Gold Level Certified**
3. Rear I/O Ports
4. 1x 3.5" Internal Drive Bay with 1x Half-height, Half-length PCI
5. OR 2x 3.5" Internal Drive Bay
6. OR 2x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI
7. OR 4x 2.5" Internal Drive Bay
8. Power Switch, Reset Button and 5x LED Indicators

GLOBAL SKU

Available Colors

Black

Chassis Manual

Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs

CSE-504-203B	SuperChassis 504-203B (Black)

Form Factor

9.8"-Depth Mini 1U chassis support for maximum motherboard size - 6.7" x 6.7"

Processor Support

Single Processor Support

Dimensions

Height	1.7" (43mm)
Width	17.2" (437mm) <<< Release form has 17.3"
Depth	9.8" (249mm)
Packaging	25.8" (W) x 6.1" (H) x 18.3" (L)
Gross Weight	10 lbs (4.5kg)
Available Colors	Black

Expansion Slots

• Up to 1x full-height, half-length PCI expansions slot*
*NOTE: Riser Card Required, See 'Drive Bays' for possible configurations

Drive Bays

Internal Bay	1x 3.5" Internal Drive Bay with 1x Half-height, Half-length PCI OR 2x 3.5" Internal Drive Bay OR 2x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI OR 4x 2.5" Internal Drive Bay Only SAS or enterprise SATA HDD recommended

Front Panel

Buttons	Power On/Off button System Reset button
LEDs	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED
I/O Ports	1x VGA, IPMI, 4xLANs, 1x COM, 4xUSB, 1xKeyboard/Mouse

Motherboard (for CSE-504-203B)

A1SAi-2550F	A1SAi-2750F
A1SRi-2558F	A1SRi-2758F
X10SBA	X10SBA-L
X10SDV-12C-TLN4F	X10SDV-16C-TLN4F
X10SDV-2C-7TP4F	X10SDV-2C-TLN2F
X10SDV-2C-TP4F	X10SDV-2C-TP8F
X10SDV-4C+-TLN4F	X10SDV-4C+-TP4F
X10SDV-4C-7TP4F	X10SDV-4C-TLN2F
X10SDV-4C-TLN4F	X10SDV-6C+-TLN4F
X10SDV-6C-TLN4F	X10SDV-7TP4F
X10SDV-7TP8F	X10SDV-8C+-LN2F
X10SDV-8C-TLN4F	X10SDV-F
X10SDV-TLN4F	X10SDV-TP8F
X10SLV-Q	X11SBA-F
X11SBA-LN4F	X9SBAA-F
X9SCAA	X9SCAA-L
X9SKV-1105	X9SKV-1125
X9SKV-B915	X9SPV-F-3217UE
X9SPV-F-3610ME	X9SPV-LN4F-3LE
X9SPV-LN4F-3QE	X9SPV-M4
X9SPV-M4-3QE	X9SPV-M4-3UE

Server(s) for SC504-203B

5017P-TLN4F	5017P-TF
5017A-EP	5017A-EF
5017K-N6	5018A-LTN4
5018D-LN4T	

Operating Environment (System)

Operating Temperature Range	5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	-40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	5% - 95% (non-condensing)

Power Supply

200W Low Noise AC-DC power supply with PFC

AC Voltage	100 - 240V, 50-60Hz, 2.6 Amp Max
+5V	8.0 Amp (max.)
+5V standby	2.0 Amp (max.)
+12V	16 Amp (max.)
-12V	0.5 Amp (max.)
+3.3V	8.0 Amp (max.)
Certification	80 PLUS GOLD — **Gold Certified**

Regulatory (Power Supply)

Power Supply Safety / EMC	USA - UL listed, FCC Canada - CUL listed CCC Certification EN 60950/IEC 60950-Compliant Europe/CE Mark Germany - TUV Certified

Components

Standard Parts List

	Part Number	Qty	Description
Chassis	CSE-504-203B	1	1U Chassis (**Black**)
Cable(s)	CBL-0260L	1	US power cord 18AWG 6ft, PBF (default for low watt)
	CBL-0235L	1	77.5cm, 16-pin to 16-pin Front Cable
I/O Shield	MCP-260-00064-0B	1	1U I/O shield for X9/X10 STD Server I/O use in SC510, SC505, SC504
Front Panel	MCP-280-81301-0N	1	Front Panel Control Board
Power Supply	PWS-203-1H	1	200W Low Noise Power Supply

Optional Parts List

	Part Number	Qty	Description
Cable(s)	CBL-0080L	-	1x 4-pin to 1x SATA Power Cable
Heatsink	SNK-P0049A4	-	1U Active CPU Heat Sink for Intel Sokcet H, H2, and H3 Motherboards
I/O Shield	MCP-260-00065-0B	-	1U I/O shield for X8 STD Server I/O use in SC510, SC505, SC504
	MCP-260-00066-0B	-	1U I/O shield for X9SPV-M4 use in SC510, SC505, SC504
	MCP-260-00068-0B	-	1U I/O shield for X9SCAA/-L use in SC510, SC505, SC504
	MCP-260-00072-0B	-	1U I/O shield for X9SKV use in SC510, SC505, SC504
	MCP-260-00076-0B	-	1U I/O shield for X10SLV-Q use in SC510, SC505, SC504
	MCP-260-00082-0B	-	1U I/O shield for H9SKV use in SC510, SC505, SC504
Fan(s)	FAN-0100L4	-	40X28MM 4-PIN PWM FAN, 8500 rpm
	MCP-320-81302-0B	-	Single fan holder for one 40x28mm fan (*Note: May order two MCP-320-81302-0B to configure a dual fan holder for optional dual fan configuration)
Hard Drive Bracket	MCP-220-00051-0N	-	Retention Bracket for 1 x 2.5" HDD
	MCP-220-00044-0N	-	Retention Bracket for up to 2x 2.5" HDD

Copyright © 2016 Super Micro Computer, Inc.
Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.