# 14-Outlet Economy Network Server Surge Protector, 15 ft. (4.57 m) Cord, 3000 Joules, 1U Rack-Mount

MODEL NUMBER: **DRS-1215**








### Highlights

- 14 outlets / 15-ft. (4.57 m) cord
- 3000 joule rating
- Adjustable rackmount hardware

### Package Includes

- DRS-1215 Surge Suppressor
- Warranty information
- Instruction manual

### Description

DRS-1215 offers surge and noise suppression in a versatile all-metal multi-mount cabinet. Detachable mounting flanges are configurable for rack-mount, wall-mount and under-counter installation. Uses only 1U when installed in any 19-inch EIA-standard rack. Includes 14 outlets (6 front/8 rear), 15-foot (4.6-meter) cord and guarded power switch to reduce the risk of accidental shutoff. Diagnostic LED indicates surge protection status.

### Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19 inch rack ("zero U" mounting possible in many racks)
- 3000 joules AC surge suppression with EMI/RFI filtering
- 14 NEMA 5-15R output receptacles (6 front/8 rear)
- 15-ft. (4.57 m) AC cord with NEMA 5-15P straight-in plug connection
- Diagnostic LED confirms suppressor operation
- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn off
- 15 amp capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332100245 |
| **INPUT** | |

| | |
|---|---|
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 120000 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 15 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 4.57 |
| Integrated Cord Clip | No |
| **OUTPUT** | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (14) 5-15R |
| Circuit Breaker (amps) | 15 |
| Right-Angle Outlets | No |
| **USER INTERFACE, ALERTS & CONTROLS** | |
| Diagnostic LED(s) | Yes |
| Switches | Power switch controls power to all outlets |
| Diagnostic LED Details | Green - Protection Present |
| Locking Switch Cover | Transparent locking switch cover prevents accidental shutoff |
| **SURGE / NOISE SUPPRESSION** | |
| AC Suppression Joule Rating | 3000 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| Safe Thermal Fusing | Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences |
| UL1449 Let Through Rating | 330V |
| EMI / RFI Filtering | 40-80 dB |
| Immunity | Conforms to IEE 587 / ANSI C62.41 |
| Automatic Shut-Off | No |
| **DATALINE SURGE SUPPRESSION** | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |

| | |
|---|---|
| **PHYSICAL** | |
| Material of Construction | Metal |
| Power Cord Color | Black |
| Form Factors Supported | 1U rackmount, 0U vertical rackmount, wallmount and under-counter mounting supported - detachable flanges can be re-configured to support a variety of additional mounting options |
| Housing Color | Black |
| Mounting Holes or Slots | No |
| Outlets Measurement (Center to Center) | Distance between front outlets = 38.9mm; Distance between rear outlets = 38.9mm |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 9.30 x 2.50 x 20.40 |
| Shipping Dimensions (hwd / cm) | 23.62 x 6.35 x 51.82 |
| Shipping Weight (lbs.) | 5.86 |
| Shipping Weight (kg) | 2.66 |
| Unit Dimensions (hwd / in.) | 1.750 x 17.500 x 4.000 |
| Unit Dimensions (hwd / cm) | 4.45 x 44.45 x 10.16 |
| Unit Weight (lbs.) | 4.6 |
| Unit Weight (kg) | 2.09 |
| Mounting Details | Includes flanges |
| **FEATURES & SPECIFICATIONS** | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| Mounting Accessory Included | Yes |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | CAN/CSA-C22.2 No. 308 (Canada); UL 1363 |
| Product Compliance | RoHS |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.