# 3.7kW Single-Phase Local Metered PDU, 208/230V (8 C13 & 2 C19), C20 / L6-20P Adapter, 12 ft. (3.66 m) Cord, 1U Rack-Mount, TAA

MODEL NUMBER: **PDUMH20HV**



### Highlights

- Local metered single phase 16A 208/230V PDU
- 1U horizontal rackmount; Digital current meter
- C20 input with L6-20P plug adapter; 12-ft. (3.66 m) line cord
- 10 total outlets (8 C13, 2 C19)
- Reversible housing; 6.5 in. / 16.5 cm depth
- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases

### Package Includes

- Rackmount PDU
- C19 to L6-20P plug adapter
- Rack mounting brackets

### Features

- 16/20A single phase 208/230V Local Metered Power Distribution Unit / rack PDU (rPDU) (Agency de-rated to 16A continuous)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- C20 inlet with C20 input cable and L6-20P adapter; 12-ft. (3.66 m) line cord
- 1U horizontal rackmount format installs in one rack space
- 10 total outlets (8 C13 / 2 C19)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
  Back panel grounding lug
- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332159014 |
| PDU Type | Local Metered |
| **INPUT** | |
| Input Phase | Single-Phase |
| PDU Input Voltage | 208; 230 |
| Recommended Electrical Service | Single-phase 16/20A 230/208V service |

| | |
|---|---|
| Maximum Input Amps | 16 |
| Maximum Input Amps Details | Agency de-rated to 16A continuous |
| Input Connection Type | C20 inlet |
| PDU Plug Type | NEMA L6-20P; IEC-320 C20 |
| Input Cord Details | Includes 12 ft. / 3.6m C19 to C20 power cable and L6-20P plug adapter |
| Input Cord Length (ft.) | 12 |
| Input Cord Length (m) | 3.66 |
| **OUTPUT** | |
| Output Capacity Details | 3.68kW (230V), 3.33kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (8) C13; (2) C19 |
| Output Nominal Voltage | 208/230V |
| **USER INTERFACE, ALERTS & CONTROLS** | |
| Front Panel LCD Display | Digital display reports total PDU output current in amps |
| **SURGE / NOISE SUPPRESSION** | |
| Automatic Shut-Off | No |
| **PHYSICAL** | |
| Material of Construction | Metal |
| Rack Height | 1U |
| Form Factors Supported | 1U rackmount. Includes mounting accessories for 2-4 post racks |
| Minimum Required Rack Depth (cm) | 24.13 |
| Minimum Required Rack Depth (inches) | 9.5 |
| PDU Form Factor | Horizontal (1U) |
| Shipping Dimensions (hwd / in.) | 2.20 x 11.60 x 20.40 |
| Shipping Dimensions (hwd / cm) | 5.59 x 29.46 x 51.82 |
| Shipping Weight (lbs.) | 7.50 |
| Shipping Weight (kg) | 3.40 |
| Unit Dimensions (hwd / in.) | 1.750 x 17.500 x 6.500 |
| Unit Dimensions (hwd / cm) | 2,87 x 44,4 x 16,5 |
| Unit Weight (lbs.) | 6.80 |
| Unit Weight (kg) | 3.08 |
| **ENVIRONMENTAL** | |

| | |
|---|---|
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | -22° to 122°F (-30° to 50°C) |
| Relative Humidity | 5% to 95% non-condensing |
| Operating Elevation | 0-10000 ft. (0-3000 m) |
| **FEATURES & SPECIFICATIONS** | |
| Grounding | Rear grounding lug |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | IEC 62368-1; RETIE (Colombia); GOST (Russia); NOM (Mexico) |
| Product Compliance | RoHS; CE (Europe); EAC (Belarus, Kazakhstan, Russia); FCC Part 15 Class A (USA); UKCA; Trade Agreements Act (TAA) |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.