Surge Suppressor- State of the art protection for every application

MODEL NUMBER: **S6-DLX**



Highlights

- 6 outlets/6 ft. cord
- 1050 joule rating
- Modem/fax surge protection
- $15,000 Ultimate Lifetime Insurance (USA, Puerto Rico and Canada only)

Package Includes

- S6-DLX Surge Suppressor
- Telephone cord
- Child Safety Covers
- Color-coded cord identifiers
- Warranty information with instruction manual

Description

The S6-DLX Surge Suppressor from Tripp Lite has 6 outlets and a 6-ft. cord with a space-saving right-angle plug. The unit has 1,050 joules of surge energy absorption to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. A telephone cord is also included. Diagnostic LEDs alert the user to potential power problems. $15,000 Ultimate Lifetime Insurance (USA & Canada Only). No warranty cards required for coverage! The Super 6 Deluxe comes with child safety covers and color-coded cord identifiers.

Features

- 6 outlets with child safety covers
- 6-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem / fax / phone equipment; 6-ft. telephone cord included
- $15,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment - No warranty cards required for coverage!
- Surge energy absorption: 1,050 joules; 42,500 amps
- 15 amp circuit breaker
- 2 diagnostic LEDs indicate AC present & line fault
- EMI/RFI noise filtering
- Keyhole supports for wall mounting
- Color-coded cord identifiers
- Lifetime product warranty

Specifications

INPUT	
Nominal Input Voltage(s) Supported	100V AC
Recommended Electrical Service	120V (110-125V)

Voltage Compatibility (VAC)	120
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	6
Right-Angle Plug	Yes
Input Cord Length (m)	1.83
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	50 / 60 Hz
Output (Watts)	1800
Output Receptacles	(6) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(2) Yes
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
Switches	Two position on/off power switch
Diagnostic LED Details	PROTECTION PRESENT, LINE OK
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1050
AC Suppression Response Time	< 1 ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC Suppression Surge Current Rating	42,500 amps
UL1449 Let Through Rating	330V - UL Verified
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587 / ANSI C62.41
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	Yes
PHYSICAL	
Color	Light Gray

Material of Construction	Plastic
Power Cord Color	Light Gray
Housing Color	Light Gray
Mounting Holes or Slots	Yes
Receptacle Color	Light gray
Unit Dimensions (hwd / in.)	1.250 x 3.250 x 8.250
Unit Dimensions (hwd / cm)	3.2 x 8.3 x 21
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	No
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	$15,000 Ultimate Lifetime Insurance

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.