# 1-Outlet Personal Surge Protector, Direct Plug-In, 600 Joules, 2 Diagnostic LEDs

MODEL NUMBER: **SPIKECUBE**












### Highlights

- 1 outlet / direct plug-in
- 600 joule rating
- Diagnostic LEDs

### Package Includes

- SPIKECUBE Surge Suppressor
- Warranty and instruction information

### Description

The SPIKECUBE Surge Suppressor is a direct plug-in suppressor providing protection on one AC outlet. Its small size makes it ideal for protecting laptop computers, projectors and other portable electronics. A green "Protected" and red "Grounded" LED illuminates to indicate that adequate surge suppression is available. The unit has 600 joules of surge energy absorption.

### Features

- 1 outlet; direct plug-in
- Surge energy absorption: 600 joules; 6,500 amps
- Diagnostic LEDs indicate protection present (green) and ground present (red)
- $5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332010643 |
| **INPUT** | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Cord Length Details | Direct Plug-In |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 36000 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 0 |

| | |
|---|---|
| Right-Angle Plug | No |
| Input Cord Length (m) | 0.00 |
| Integrated Cord Clip | No |
| **OUTPUT** | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (1) 5-15R |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (1) Yes |
| Right-Angle Outlets | No |
| **USER INTERFACE, ALERTS & CONTROLS** | |
| Diagnostic LED(s) | Yes |
| Diagnostic LED Details | Protected (green) & Grounded (red) |
| **SURGE / NOISE SUPPRESSION** | |
| AC Suppression Joule Rating | 600 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating | 400, 500, 500 |
| Automatic Shut-Off | No |
| **DATALINE SURGE SUPPRESSION** | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| **PHYSICAL** | |
| Material of Construction | Plastic |
| Form Factors Supported | Direct plug in suppressor supports wall-mounting directly into AC receptacle |
| Housing Color | Light Gray |
| Mounting Holes or Slots | No |
| Receptacle Color | Gray |
| Shipping Dimensions (hwd / in.) | 6.50 x 4.00 x 2.00 |
| Shipping Dimensions (hwd / cm) | 16.51 x 10.16 x 5.08 |
| Shipping Weight (lbs.) | 0.23 |
| Shipping Weight (kg) | 0.10 |

| | |
|---|---|
| Unit Dimensions (hwd / in.) | 2.500 x 1.900 x 1.800 |
| Unit Dimensions (hwd / cm) | 6.35 x 4.83 x 4.57 |
| Unit Weight (lbs.) | .100 |
| Unit Weight (kg) | 0.05 |
| **FEATURES & SPECIFICATIONS** | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | cUL Listed; UL 1449; UL Listed |
| Product Compliance | RoHS |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | $5,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>  |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.