3 Breaker Maintenance Bypass Panel for SVX60K_, S3M60KX, SU60KX, SU60KTV

MODEL NUMBER: **SU60KMBPKX**



Highlights

- Wallmount manual bypass panel isolates UPS from connected loads for maintenance with no loss of network availability
- Includes Kirk-Key interlock system enhances system reliability
- 3 built-in circuit breakers, heavy duty buswork
- Compatible with select Tripp Lite 3 phase UPS systems

Description

Wallmount 3 breaker manual bypass panel with Kirk Key interlock system isolates the UPS from connected loads for maintenance with no loss of network availability. 125A breaker with KAIC rating of 35. Key included.
Compatible with Tripp Lite SVX60K_, S3M60KX, SU60KX, SU60KTV

Features

- Wallmount 3 breaker manual bypass panel with Kirk Key interlock system
- Isolates the UPS from connected loads for maintenance with no loss of network availability
- 125A breaker with KAIC rating of 35
- Key included
- Compatible with Tripp Lite SVX60K_, S3M60KX, SU60KX, SU60KTV

Specifications

OVERVIEW	
UPC Code	037332146311
Accessory Type	Bypass Panel
Accessory Class	UPS Accessories
INPUT	
Nominal Input Voltage(s) Supported	480V AC
Voltage Compatibility (VAC)	480
PHYSICAL	
Form Factors Supported	Wallmount

Shipping Dimensions (hwd / in.)	43.20 x 30.87 x 12.50
Shipping Dimensions (hwd / cm)	109.73 x 78.41 x 31.75
Shipping Weight (lbs.)	225.00
Shipping Weight (kg)	102.06
Unit Dimensions (hwd / in.)	42.360 x 30.120 x 11.750
Unit Dimensions (hwd / cm)	107.6 x 76.5 x 29.8
Unit Weight (lbs.)	220
Unit Weight (kg)	99.79
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.