# PAC-UNIV-D9F-D9F-10M

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Similar to illustration

## General ordering data

| | |
|---|---|
| Version | Pre-assembled cable, PAC, Cable LiYCY, 7,8 ± 1 mm |
| Order No. | 1349870100 |
| Type | PAC-UNIV-D9F-D9F-10M |
| GTIN (EAN) | 4032248238385 |
| Qty. | 1 pc(s). |

# PAC-UNIV-D9F-D9F-10M

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

| | |
|---|---|
| Net weight | 1,043 g |

### Temperatures

| | | | |
|---|---|---|---|
| Storage temperature | -10...60 °C | Operating temperature | -10...50 |

### General Data

| | | | |
|---|---|---|---|
| Cable | Cable LiYCY | Cable length | 10 |
| Connector PLC side | SUB-D FEMALE 9P | Interface connector | SUB-D FEMALE 9P |
| Material | PVC | Number of poles, min. | 9-pole |
| Outer diameter | 7,8 ± 1 mm | Suitable for | Analogue signals |
| Wire cross-section | 0.25 mm² | | |

### Electrical Data

| | | | |
|---|---|---|---|
| Capacity wire / shield | 300 pF/m | Capacity wire / wires | 300 pF/m |
| Operating voltage | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path, max. | 1 A |
| Rated voltage | ≤ 60 Vdc ≤ 25 Vac | Resistance | ≤ 80 mΩ/m |
| Total current, max. | 3 A | | |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 6.0 | EC000237 | ETIM 7.0 | EC000237 |
| ETIM 8.0 | EC000237 | ETIM 9.0 | EC000237 |
| ECLASS 9.0 | 27-24-22-20 | ECLASS 9.1 | 27-24-22-20 |
| ECLASS 10.0 | 27-24-22-20 | ECLASS 11.0 | 27-24-22-20 |
| ECLASS 12.0 | 27-24-22-20 | ECLASS 13.0 | 27-24-22-20 |
| ECLASS 14.0 | 27-24-22-20 | | |

### Environmental Product Compliance

| | |
|---|---|
| REACH SVHC | / |
| RoHS Compliance Status | Compliant |

### Approvals

| | |
|---|---|
| ROHS | Conform |

### Downloads

| | |
|---|---|
| Catalogues | Catalogues in PDF-format |