EPAK-CI-VO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



The analogue converters of the EPAK series are characterised by their compact design.
The wide range of functions available with this series of analogue converters make them suitable
for applications which do not require international approvals.
Properties:

- Safe isolation, conversion and monitoring of your analogue signals
- Configuration of the input and output parameters directly on the device via DIP switches
- No international approvals
- High interference resistance

General ordering data

Order No.	7760054176
Type	EPAK-CI-VO
GTIN (EAN)	6944169701474
Qty.	1 pc(s).

EPAK-CI-VO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Dimensions and weights

Depth	89 mm	Depth (inches)	3.504 inch
Width	17.5 mm	Width (inches)	0.689 inch
Length	100 mm	Length (inches)	3.937 inch
Net weight	80 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-20 °C...60 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1	SCIP	6a722fc5-2d22-41b4-9544-5b95e45

Input

Input current	4...20 mA	Input resistance, current	≤ 100 Ω
Number of inputs	1		

Output

Number of outputs	1	Output voltage, note	0...10 V
load impedance voltage	≥ 10 kΩ		

General data

Accuracy	0.15 % v. FSR	Configuration	none
Galvanic isolation	between input / output / supply	Power consumption	<60mA @ 24VDC
Step response time	≤ 100 ms	Temperature coefficient	≤ 150 ppm/K
Type of connection	Screw connection	Voltage supply	20...30 V DC

Insulation coordination

EMC standards	EN 61326	Galvanic isolation	between input / output / supply
Impulse withstand voltage	3 kV (1.2/50µs)	Insulation voltage	2 kV_{eff}
Pollution severity	2	Rated voltage	300 V AC_{rms}
Surge voltage category	III		

Connection data

Type of connection	Screw connection	Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.6 Nm	Clamping range, rated connection	2 mm²
Clamping range, min.	0.5 mm²	Clamping range, max.	2 mm²
Wire connection cross section AWG, min.	AWG 30	Wire connection cross section AWG, max.	AWG 14

Classifications

ETIM 6.0	EC002653	ETIM 7.0	EC002653
ETIM 8.0	EC002653	ECLASS 9.0	27-21-01-20
ECLASS 9.1	27-21-01-90	ECLASS 10.0	27-21-01-20
ECLASS 11.0	27-21-01-20	ECLASS 12.0	27-21-01-20

EPAK-CI-VO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Approvals

Approvals	CE
ROHS	Conform

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	CAD data – STEP
User Documentation	Instruction sheet
Catalogues	Catalogues in PDF-format

EPAK-CI-VO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Drawings



